Elsevier Editorial System(tm) for Proceedings of the Combustion Institute Manuscript Draft

Manuscript Number: PROCI-D-15-00738R2

Title: Scalar dissipation rate and scales in swirling turbulent premixed flames

Article Type: Research Paper

Section/Category: Turbulent Flames

Keywords: Turbulent premixed flame; Scalar dissipation rate; Dissipative structures; Swirl burner; 2D Rayleigh scattering

Corresponding Author: Dr. M. Mustafa Kamal, PhD

Corresponding Author's Institution: University of Cambridge

First Author: M. Mustafa Kamal, PhD

Order of Authors: M. Mustafa Kamal, PhD; Bruno Coriton, PhD; Ruigang Zhou, PhD; Jonathan H Frank, PhD; Simone Hochgreb, PhD

Abstract: Simultaneous Rayleigh scattering and OH-PLIF imaging measurements of temperature and OH were used to investigate the properties of turbulent premixed flames, including the nature of the 2D thermal structures and scalar dissipation rate in the Cambridge/Sandia swirling bluff body stabilized flames, with and without the effect of swirl. Swirl creates enhanced turbulence as well as outer flow entrainment, and disrupts the pre-flame zone significantly, whilst the high temperature reaction zone as marked by OH remains relatively intact. In particular, the temperature at the location of maximum OH gradient shows very low variance across the flame region. The 2D image analysis of OH and temperature shows that the corresponding 2D gradients are aligned up to a distance of half the laminar flame thickness away from the flame front, deviating significantly in the case of swirling flames beyond that region. As in previous investigations in diffusion flames, the mean width of the observed thermal structures increases from 300 to 600 microns near the flame, with a main mode around the laminar flame thermal width in the unswirled case. The correlation between 2D thermal fluctuation gradients and variance extracted from the images shows a direct proportionality, with a slope which agrees well with theory in the region of high turbulence away from the base. At the base of the flame where turbulence is low, the local scalar dissipation becomes a function of the local temperature via the thermal diffusivity.

Scalar dissipation rate and scales in swirling turbulent premixed flames

M. Mustafa Kamal^{a,c*}, Bruno Coriton^b, Ruigang Zhou^a, Jonathan H. Frank^b, Simone Hochgreb^a

^a Department of Engineering, University of Cambridge, CB2 1PZ, Cambridge, UK ^b Combustion Research Facility, Sandia National Laboratories, Livermore, CA 94551, USA ^c Department of Mechanical Engineering, University of Engineering and Technology, Peshawar, Pakistan

Corresponding author:	M. Mustafa Kamal
	Department of Engineering, University of Cambridge
	Cambridge, CB2 1PZ, United Kingdom
	Fax: (+44) (0) 1223 764311
	Email: mustafa.kamal@cantab.net
Colloquium topic: 5.	Turbulent flames

Alternative Colloquium topic: 3. Diagnostics

Paper length (method 1):

Main Text:	word processor count	=3538
Equations:	(0+0) x (7.6 words/line) x (1 columns)	= 0
References:	$(35+2) \times (2.3 \text{ lines/reference}) \times (7.6 \text{ words/line})$	= 623
Tables:	(7+4) x (7.6 words/line) x (1 columns)	= 84

Figures: Word count = (figure height in mm + 10 mm) x (2.2 words/mm) x (#columns) + (#words in caption)

Figure 1:	$(60 \text{ mm}+10) \times (2.2 \text{ words/mm}) \times (1 \text{ column}) +24$	= 178
Figure 2:	$(33 \text{ mm}+10) \times (2.2 \text{ words/mm}) \times (1 \text{ column}) +38$	= 132
Figure 3:	$(139 \text{ mm}+10) \times (2.2 \text{ words/mm}) \times (1 \text{ column}) +41$	= 368
Figure 4:	$(71 \text{ mm}+10) \times (2.2 \text{ words/mm}) \times (1 \text{ column}) +33$	= 211
Figure 5:	$(104 \text{ mm}+10) \times (2.2 \text{ words/mm}) \times (1 \text{ column}) +56$	= 306
Figure 6:	$(79 \text{ mm}+10) \times (2.2 \text{ words/mm}) \times (1 \text{ column}) +14$	= 209

*Corresponding author

Email address: mustafa.kamal@cantab.net

Figure 7: $(104 \text{ mm}+10) \times (2.2 \text{ words/mm}) \times (1 \text{ column}) +10 = 260$

Figure 8: $(115 \text{ mm}+10) \times (2.2 \text{ words/mm}) \times (1 \text{ column}) +57 = 333$

Total figures: 1965

Total = 6242 words

Color reproduction: online only (color figures are to be printed in gray scale)

Rebuttal

We thank the reviewers for the kind remarks and useful criticisms, which have led some minor corrections to the manuscript. Specific points are addressed below.

Reviewer 1:

I have read through the extensive revisions the authors have made and they have essentially adequately addressed all of my concerns and improved the paper.

However I am still not satisfied with the assertion in the paper and the response to 2) "There is at the moment no direct experimental confirmation of the change in reaction rates with turbulence intensity and length scale." There are in fact published experiments that show this under premixed conditions."

My issue here is that there are several published papers using laser diagnostic measurements of heat release proxies (typically CH2OxOH) in premixed flames that do show in interaction and reduction in heat release as a function of turbulence. These papers are not cited in the text and if they were the above statement could not be made. Such papers come from a broad range of groups: Michigan (Temme Driscoll), Sydney (Dunn Masri Bilger), Lund (Zhao Alden Bai) and Cambridge (Mastorakos).

Reply: We agree that there are a number of experiments that qualitatively address the change in reaction rate with turbulence (Temme, Driscoll, Dunn, Masri, Bilger, Zhao Alden Bai) or semiquantitatively with acoustic frequencies (Mastorakos). Since there is nothing in the present paper that particularly requires the statement, we have modified the referred sentence to (lines 2-6 page 6):

"A number of experiments have attempted to connect the effects of turbulence intensity and integral length scale to the behaviour of surrogate scalars, showing for example a widening distribution of intermediates such as formaldehyde with increasing turbulence [1] [18] [19] [20] [21] [22]. A full description of the interaction between turbulence and reaction rate remains a key problem in combustion. "

Reviewer 2:

As noted before, the experiments were well and carefully done, but the write-up still seems to me to be lacking in some respects. In my original review, I noted that the Conclusion section should be strengthened, and while it has been modified (to address another aspect of the work), it still seems to me to be weak. In fact, the Abstract has more info than the Conclusion. Some specific comments are given below:

We have re-read the manuscript, and reworded passages that seemed redundant or unclear.

1. The authors start off the paper by stating that "The rate of mixing of the products with reactants has a direct contribution to the overall reaction rate in turbulent premixed flames." This is a restatement of the original opening sentence but is still inaccurate. In my original review, I reminded the authors that reactants and products do not necessarily mix in a premixed turbulent flame. That is, in flames that are attached and do suffer extinction, reactants and products do not mix, but I realize that in other cases (like the one studied here),

reactants and products do mix (and this is part of the stabilization mechanism). Anyway, a more accurate opening sentence is still needed.

It is not clear what is confusing the reviewer. Clearly, in order for reactions to take place, products (and temperature) diffuse at the microscale to produce reaction. This micromixing takes place in the sense that is meant by modellers, i.e. that the *scalar dissipation rate controls the reaction rate in the limit of high Re, high Da limit, and only partially controls it away from that limit*. This of course does not mean that reactants and product mix *and only then* go through a premixed flame, as would for example be the case in a partially extinguished flame. This is not the case here, as the turbulence levels are very low and there is no extinction, but of course the rate of turbulent micromixing controls the extent of overall reaction per unit volume in a premixed flame. Although we believe the original statement is just fine, we propose a rewording in case this is not clear, to: "The rate of turbulent micromixing between hot products and reactants controls the overall rate of heat release per unit volume in a flame". We trust that this is acceptable.

2. The authors state that the burner is described in detail in ref 25 and is shown schematically in Fig. 1. This is no longer the case: the flowfield is shown, but there is no schematic of the burner.

A correction has been made to the statement, in lines 10-11, page 7.

3. In the Experimental section the authors state that the Rayleigh scattering and OH PLIF are overlapped by vertical stacking far from the imaged section. I cannot figure out what "vertical stacking" refers to.

The sentence has been reworded to (page 9, 5-6): "The expanded laser beams used for Rayleigh scattering and OH-PLIF were overlapped by stacking the beam planes crossing the centreline of the burner along the axial direction".

4. In the opening paragraph of Data analysis, the authors state that the maximum gradient of OH LIF is often close to the location of peak heat release. Shouldn't a reference have been given here?

A reference to justify the choice has been added to the manuscript, http://dx.doi.org/10.1017/S0022112094003010

5. On page 15, the authors state "...it is possible to reproduce these quantities (Fig. 10) in the form of the normalized Favre averaged scalar dissipation..." What Fig. 10 are they referring to? This paper does not have 10 figures.

We thank the reviewer for identifying the typo. The correct figure number is Fig. 8. The figure number has been corrected in the manuscript.

6. Below this paragraph, the authors make reference to "The theory and DNS predictions for the relevant constant suggest that the slope of the curve should scale as ..." There are no references given for the theory or DNS that they refer to (but there should have been).

The reference is to Ref. [30] in this version of the manuscript, as refered to on the previous sentence. (H. Kolla, J. W. Rogerson, N. Chakraborty, and N. Swaminathan, Combust. Sci. Tech. 181 (2009) 518-535.)

Reviewer 3:

The authors have adequately addressed the points raised in my initial review. I now consider this manuscript acceptable for publication in the Proceedings.

Reply: We thank the reviewer for his recommendation for publication.

Editorial comments:

Reviewers 1 and 2 still feel that the paper can be improved before publication. In particular, pay attention to Reviewer 2 that points out several inconsistencies between what is stated in the text and what figures/content are actually present in the manuscript. Also, the authors should carefully read the text to avoid typographical errors and missing punctuation (multiple cases were noted upon inspection).

Reply:

Thank you. We have re-read the manuscript completely to make sure that these comments are have been addressed appropriately. Sections where wording has been changed have been highlighted in the final manuscript.

Scalar dissipation rate and scales in swirling turbulent premixed flames

M. Mustafa Kamal^{a,c*}, Bruno Coriton^b, Ruigang Zhou^a, Jonathan H. Frank^b, Simone Hochgreb^a

^a Department of Engineering, University of Cambridge, CB2 1PZ, Cambridge, UK ^b Combustion Research Facility, Sandia National Laboratories, Livermore, CA 94551, USA ^c Department of Mechanical Engineering, University of Engineering and Technology, Peshawar, Pakistan

Corresponding author:	M. Mustafa Kamal			
	Department of Engineering, University of Cambridge			
	Cambridge, CB2 1PZ, United Kingdom			
	Fax: (+44) (0) 1223 764311			
	Email: mustafa.kamal@cantab.net			
Colloquium topic: 5.	Turbulent flames			

Alternative Colloquium topic: 3. Diagnostics

Paper length (method 1):

Main Text:	word processor count	=3538
Equations:	(0+0) x (7.6 words/line) x (1 columns)	= 0
References:	$(35+2) \times (2.3 \text{ lines/reference}) \times (7.6 \text{ words/line})$	= 623
Tables:	(7+4) x (7.6 words/line) x (1 columns)	= 84

Figures: Word count = (figure height in mm + 10 mm) x (2.2 words/mm) x (#columns) + (#words in caption)

Figure 1:	$(60 \text{ mm}+10) \times (2.2 \text{ words/mm}) \times (1 \text{ column}) +24$	= 178
Figure 2:	$(33 \text{ mm}+10) \times (2.2 \text{ words/mm}) \times (1 \text{ column}) +38$	= 132
Figure 3:	$(139 \text{ mm}+10) \times (2.2 \text{ words/mm}) \times (1 \text{ column}) +41$	= 368
Figure 4:	$(71 \text{ mm}+10) \times (2.2 \text{ words/mm}) \times (1 \text{ column}) +33$	= 211
Figure 5:	$(104 \text{ mm}+10) \times (2.2 \text{ words/mm}) \times (1 \text{ column}) +56$	= 306
Figure 6:	$(79 \text{ mm}+10) \times (2.2 \text{ words/mm}) \times (1 \text{ column}) +14$	= 209

*Corresponding author *Email address:* mustafa.kamal@cantab.net Figure 7: $(104 \text{ mm}+10) \times (2.2 \text{ words/mm}) \times (1 \text{ column}) +10 = 260$

Figure 8: $(115 \text{ mm}+10) \times (2.2 \text{ words/mm}) \times (1 \text{ column}) +57 = 333$

Total figures: 1965

Total = 6242 words

Color reproduction: online only (color figures are to be printed in gray scale)

Scalar dissipation rate and scales in swirling turbulent premixed flames 1 2 M. Mustafa Kamal^{a,c*}, Bruno Coriton^b, Ruigang Zhou^a, Jonathan H. Frank^b, Simone Hochgreb^a 3 4 ^a Department of Engineering, University of Cambridge, CB2 1PZ, Cambridge, UK 5 ^b Combustion Research Facility, Sandia National Laboratories, Livermore, CA 94551, USA 6 7 ^c Department of Mechanical Engineering, University of Engineering and Technology, Peshawar, Pakistan 8 9 10 Abstract 11

12 Simultaneous Rayleigh scattering and OH-PLIF imaging measurements of temperature and OH were used to investigate the properties of turbulent premixed flames, including the 13 14 nature of the 2D thermal structures and scalar dissipation rate in the Cambridge/Sandia 15 swirling bluff body stabilized flames, with and without the effect of swirl. Swirl creates enhanced turbulence as well as outer flow entrainment, and disrupts the pre-flame zone 16 significantly, whilst the high temperature reaction zone as marked by OH remains relatively 17 18 intact. In particular, the temperature at the location of maximum OH gradient shows very low 19 variance across the flame region.

20 The 2D image analysis of OH and temperature shows that the corresponding 2D 21 gradients are aligned up to a distance of half the laminar flame thickness away from the flame front, deviating significantly in the case of swirling flames beyond that region. As in previous 22 investigations in diffusion flames, the mean width of the observed thermal structures 23 increases from 300 to 600 microns near the flame, with a main mode around the laminar 24 flame thermal width in the unswirled case. The correlation between 2D thermal fluctuation 25 gradients and variance extracted from the images shows a direct proportionality, with a slope 26 27 which agrees well with theory in the region of high turbulence away from the base. At the

*Corresponding author *Email address:* mustafa.kamal@cantab.net

- base of the flame where turbulence is low, the local scalar dissipation becomes a function of
 the local temperature via the thermal diffusivity.
- 3
- 4
- 5 Keywords: Turbulent premixed flame; Scalar dissipation rate; Dissipative structures; Swirl
- 6 burner; 2D Rayleigh scattering

1 1. Introduction

2 The rate of turbulent micromixing between hot products and reactants controls the overall 3 rate of heat release per unit volume in a flame [1] [2]. In the limit of fast reactions at high Damköhler number (Da), the reaction rate becomes proportional to the scalar dissipation rate. 4 5 and the flame thickness becomes much smaller than the turbulent spatial scales. Under this 6 thin flame regime, the assumption is often made that the reaction region remains intact, while 7 the reacting interface is transported and extended by turbulence; the reaction rate becomes 8 proportional to the rate at which the flame front propagates through the mixture. This is 9 expressed via the flame surface density [1] [3] [4], or via the rate of scalar dissipation, 10 characterized by the rate of micromixing of the relevant scalar fluctuation [5] [6] [7] [8]. The mean Favre-averaged scalar dissipation rate of a progress of reaction c, is denoted as 11 $\tilde{\chi}_c = \overline{\rho D \nabla c^{"} \nabla c^{"}} / \bar{\rho}$, where ρ and D are the mixture density and scalar diffusivity, and the 12 usual notation is used: bars for average, tilde for density averaged and double primes for 13 14 turbulent fluctuation away from the local Favre mean.

15 Many previous experimental studies have explored the internal structure of premixed 16 turbulent flames, to understand under what conditions the reaction zone structure may be affected by turbulence. A number of studies measured a thickening of the preheating zone 17 18 (also known as thermal or pre-flame zone) due to enhanced transport caused by structures 19 smaller than the preheating zone [9] [10] [11] [12], whereas others [13] [14] suggest a thinning effect. In references [13] [14], simultaneous OH planar laser-induced fluorescence 20 21 (PLIF) and Rayleigh scattering imaging were used to show that for Karlovitz (Ka) numbers 22 up to 20, the reaction zone is undisturbed; subsequent studies showed that much higher 23 values are required to disrupt the flame zone [15].

Direct numerical simulations of high Ka turbulent flames by Aspden *et al.* [16] and Poludnenko and Oran [17] show that although the pre-flame zone is significantly disrupted, the reaction zone remains rather undisturbed, and that the main effect of turbulence is the wrinkling of the reaction zone. A number of experiments have attempted to connect the effects of turbulence intensity and integral length scale to the behaviour of surrogate scalars, showing for example a widening distribution of intermediates such as formaldehyde with increasing turbulence [1] [18] [19] [20] [21] [22]. A full description of the interaction between turbulence and reaction rate remains a key problem in combustion.

7 Previously, Chen and Bilger [12] combined single-plane measurements of OH and two-8 plane measurements of temperature to study the structure of turbulent methane, propane and 9 hydrogen Bunsen flames, for Karlovitz numbers of up to 3 in the hydrocarbon flames and 10 10 in hydrogen flames. These measurements quantified the gradients of temperature, scalar dissipation and a number of statistical properties of these Bunsen flames [12]. Frank and 11 Kaiser used similar techniques with higher resolution [23] [24] for measurements of thermal 12 13 dissipation rate and length scales in diffusion flames. Wang et al. [25] [26] analysed the 14 resolution requirements for separating noise from signal in scalar dissipation measurements.

15 The present measurements are based on the same techniques developed by Frank and 16 Kaiser [23] [24] for measurements of thermal dissipation rate and corresponding length scales in diffusion flames. The present imaging measurements address the scalar structures in the 17 swirling, bluff-body stabilized methane V-flames extensively described by Sweeney et al. 18 19 [11], at Ka numbers up to 7. These complement previous measurements in turbulent 20 premixed and stratified flames by Sweeney et al. [11] [27] [28] using line Raman/Rayleigh/CO-LIF and cross-planar OH-PLIF techniques. The latter provided detailed 21 22 information on local concentrations of major species and temperature, as well as the local temperature gradients at the flame along a line, and corresponding 3D gradients at the flame 23 24 front. However, such line measurements cannot offer insight into the detailed structure of 25 mixing and scalar dissipation rate in the flow.

In the present work, we use high resolution Rayleigh scattering and OH LIF imaging to measure the 2D length scales of the characteristic structures, as well as the 2D thermal dissipation rate, for the same premixed flames at no swirl and high swirl conditions. The analysis also examines the assumption of alignment between the temperature and OH gradient, used in previous papers [11], and the robustness of the relationship between dissipation rate and variance suggested by turbulent combustion models [6] [29] [30].

7

8 **2. Experimental details**

9 2.1. Cambridge/Sandia stratified swirl burner and operating conditions

10 The geometry of the swirl burner is described in detail in Ref. [28]. Long co-annular tubes 11 ensure that a well-developed turbulent flow is delivered to the flame region. A ceramic 12 central bluff body is used to stabilize the flame with minimal heat loss. Flow through the 13 outer annulus is split between an axial and a swirling flow emerging at the base of the burner, 14 providing a maximum swirl flow ratio (SFR) of 0.33 [28].

Imaging measurements were performed at the three locations indicated by the field of view (FOV) regions in Fig. 1. Each field of view is approximately centered at the local midpoint of the flame brush, with dimensions of $24.5 \times 16.3 \text{ mm}^2$ and centreline coordinates as listed in Table 1. A subset of the previously used operating conditions in Ref. [28] is studied in this paper, focusing on comparisons between non-swirling (SFR=0%) and highly swirling (SFR=33%) flames, with no stratification between the inner and outer annuli, with a premixed equivalence ratio of ϕ =0.75 (Table 2).

22

Case	SFR (%)	S (-)	FOV 1	FOV 2	FOV 3
SwB1	0	0.03	(05, 15)	(08, 30)	(11, 50)
SwB3	33	0.54	(13, 15)	(21, 30)	(27, 50)

Table 1. Operating conditions for the flames considered. The velocity of the inner channel is $U_i = 8.3$ m/s (Re_i = 5960) and for the outer channel, $U_o = 18.7$ m/s, (Re_i = 11500 based on hydraulic diameter of the outer annulus) with co-flow velocity $U_{co} = 0.4$ m/s. Coordinates of the center of the FOV in radial and axial distances from the centreline at the base of the burner, in mm. SFR: ratio of incoming tangential to total flow rate.

6

Flames	$\frac{U'}{S_L}$			
z (mm)	2	10	30	50
SwB1	11.5	9.7	10.0	9.8
SwB3	31.8	27.5	17.9	12.9

8 **Table 2.** Maximum value of the ratio for the total mean velocity fluctuation U' divided by the 9 laminar speed S_L for a given axial location, *z*. Turbulent velocity measurements acquired with laser 10 Doppler anemometry (LDA) and particle image velocimetry (PIV) by Zhou *et al.* [28].

11

7

12 2.2. Optical arrangement

Simultaneous Rayleigh scattering and OH-PLIF imaging measurements were performed
in the Advanced Imaging Laboratory at Sandia National Laboratories. The experimental
arrangement consisted of the high-resolution Rayleigh imaging apparatus described in Ref.
[31], combined with an additional laser/camera system for simultaneous OH-PLIF imaging
[23].

A laser sheet (100 μ m thickness) used for Rayleigh scattering was produced from a frequency-doubled Nd:YAG laser, with an energy of 2.0 J/pulse at 532 nm at a repetition rate of 10 Hz. OH PLIF was excited by the frequency-doubled output of a 10-Hz Nd:YAGpumped dye-laser tuned to 283.01 nm to pump the Q₁(6) transition of the A-X(1,0) band of OH using 1.2 mJ/pulse.

Rayleigh scattering from the probe volume was imaged onto an unintensified interline transfer CCD camera (SensiCam QE, PCO/Cooke). A second interline-transfer camera was

used to image Rayleigh scattering from the air co-flow adjacent to the burner to account for
shot-to-shot variations in the laser profile. The Rayleigh scattering from room temperature air
was used as a reference signal. The background signal was extracted from measurements in
pure air and helium streams which have known Rayleigh scattering cross sections.

5 The expanded laser beams used for Rayleigh scattering and OH-PLIF were overlapped by stacking the beam planes crossing the centreline of the burner along the axial direction. The 6 7 OH fluorescence emission was imaged onto an intensified CCD camera (Andor DH312T-8 18H-83). The shot-to-shot laser energy fluctuations of $\pm 2\%$ were negligible for the subsection 9 of the dye-laser beam that was used for PLIF imaging. The OH-PLIF images were corrected 10 for variations in the average dye-laser beam profile. The FOV of the Rayleigh camera was a 19.3x14.6 mm² subsection of the 24.5x16.3 mm² region imaged by the OH-PLIF camera. The 11 12 pixel resolution of the Rayleigh scattering measurement was 14 µm/pixel. The resolution of 13 the OH-PLIF camera was approximately 140 µm/pixel and was limited by the resolution of 14 the image intensifier.

Both OH PLIF images and Rayleigh images were smoothed using a Gaussian filter, with the latter relying on a variable, temperature-dependent kernel as described in [31] [24]. Additional information regarding the image processing and system setup are detailed in the relevant references. A fixed Rayleigh scattering cross section equal to 1.09 times that of air was used to determine the temperature for all conditions in Table 1. The maximum uncertainty in the temperature measurement resulting from composition variations was estimated as $\pm 3-4\%$.

1 **3. Data analysis**

Figures 2a and 2b show an example of normalized OH LIF signal and the temperature obtained from the Rayleigh scattering signal, respectively. The flame front location is defined here as the location of the maximum gradient of the OH PLIF signal [32], and is indicated by a black line in the figure. For the present comparisons, this definition provides a well defined reference that is expected to be near the location of peak heat release rate [32]. The local flame normal is defined with respect to the flame front contour, and is shown as white dashed lines in the figure.

9 Local ensemble averaged temperatures $\langle T \rangle$ and the corresponding root mean squared 10 temperature fluctuations $\langle T' \rangle$ are obtained from 2000 individual shots for each FOV. A 11 local flame temperature T_f is defined as the instantaneous temperature at the flame front. 12 Deviations of temperature relative to the instantaneous local flame temperature are defined 13 along the normal coordinate *n*, as $T'_f = T - T_f$, with corresponding mean and rms values, 14 $\langle T_f \rangle$ and $\langle T'_f \rangle$, respectively.

The 2D temperature gradients $\nabla T = \frac{dT}{dr}\mathbf{i} + \frac{dT}{dz}\mathbf{k}$ are determined via first order central 15 differencing after filtering. The gradients of the temperature fluctuations are defined as 16 $\nabla T' = \nabla (T - \langle T \rangle)$. In previous line measurements [11], the 3D temperature gradients 17 18 throughout the flame were assumed to be parallel to the flame normal obtained from the cross 19 planar OH PLIF measurements. Here we assess the quality of this assumption in 2D by 20 determining the statistics of the angle θ between the temperature and OH gradients as a function of temperature. Further, the characteristic 2D thermal diffusion width, λ_D , of the 21 22 dissipation layer is obtained from the images. The diffusion width is defined as the full width at 20% of the local maximum temperature gradient, as determined along the direction normal 23 24 to the layer, which provides a more direct measure of the structure length scale than is 25 possible with 1D measurements [24]. The value of the thermal diffusivity, α , is obtained by 1 interpolating a lookup table of calculated values as a function of temperature from premixed 2 unstrained flames at premixed conditions of ϕ =0.75.

3

4 **4. Results and discussion**

5

6 4.1. Single shot measurements

7 Single shot images of OH PLIF signal, temperature and respective fluctuations for both 8 flow conditions at the regions nearest to the base, FOV1 (bottom panel), and furthest away, 9 FOV3 (top panel), are shown in Fig. 3. For the non-swirling case, SwB1, a comparison of the 10 temperature and OH PLIF images shows that the overall topologies of the OH-PLIF images are well aligned with the temperature images, even in the furthest downstream regions where 11 turbulence is more developed. The flame front contour (location of the highest gradient OH 12 signal) overlaps almost exactly with an isotherm at approximately 1450 K throughout the 13 14 flame region, with a thermal thickness that is only slightly larger than the laminar flame 15 thickness of $\delta_L = 588 \,\mu\text{m}$ calculated for $\phi = 0.75$.

16 Contrast this behavior with the swirling case, SwB3 (Fig. 3, right), in which the preheating region is highly disrupted and convoluted, particularly in the region further 17 downstream (FOV3): regions of high temperature appear in the reactant region, which could 18 19 be a result of out-of-plane motion of neighboring regions of the flame, as well as entrainment 20 of the flame structures into the reaction zone. The product temperatures are lower than in SwB1 as a result of the swirl-induced entrainment of co-flow air into the central product zone 21 22 [11] [28]. The OH PLIF signal boundary and the corresponding flame contour is significantly distorted but not dispersed throughout the pre-heating zone. Although the OH radical is not a 23 definitive marker of the flame location under all conditions, the distribution of the OH PLIF 24

signal is very different from that of the temperature. For temperatures above 1200 K, there
 are no clearly detectable thermal structures.

The third row in each panel of Fig. 3 shows the instantaneous fluctuation, *T'*, relative to the local mean temperature for the two regions FOV 1 and FOV 3. The highest deviations from the mean temperature straddle the location of the flame, as expected.

6

7 4.2. Flame temperature statistics

8 Figure 4 shows ensemble mean temperatures and rms fluctuations along the coordinate 9 normal to the flame, n, where n=0 is the flame front defined as the location of maximum gradient in the OH LIF signal. The variance is lowest at n=0, increases to a maximum away 10 11 from the flame front, and eventually decreases to zero in the products and reactants. Laminar 12 unstrained premixed flame simulations at $\phi = 0.75$ (based on GRI Mech 3.0 [33] and full 13 transport properties) are also shown. The measured maximum conditional mean temperatures in the present dataset appear to be systematically lower than the calculated adiabatic flame 14 temperature (which agrees well with the line measurements in [11]), by 150 K in the non-15 swirl case. The sources of the discrepancies are unclear, as all calibrations and procedures 16 17 have been checked.

The mean product temperature in the swirling case SwB3 is lower than the corresponding non-swirling case SwB1 owing to entrainment. The fluctuation in temperature is significantly increased by the addition of swirl, particularly in the pre-flame region, due to entrainment of air, both around the outer edges of the flame, as well as through the top in the open recirculation zone [11] [28]. The low fluctuation in temperature at the flame front shows that the location of peak OH gradient, and presumably the reaction zone, is tied to a particular temperature, indicating that the flames appear as curved and strained flamelets.

25

1 4.3. Temperature and OH 2D gradient alignment

2 Since temperature and OH are the most easily imaged scalars, these are often used as 3 surrogates for progress of reaction markers [13] [14] [27] [34]. However, it is clear that their 4 behaviour in the present flames can be very different, and that isocontours of temperature do not always align with those of OH LIF signals. In the present study, it is possible to identify, 5 6 in 2D, how well the isoscalars align around the flame. In particular, in the study using line 7 measurements [11], two-plane OH LIF imaging was used to determine the orientation of the 8 3D flame normal for the flame crossing the measurement line. This orientation was then used 9 to correct the temperature gradient along the measurement line, under the assumption that the 10 OH contour is parallel to the temperature contour in the vicinity of the thermal zone. Figure 5 11 shows how well this assumption holds by evaluating the angle between the normal directions for contours of temperature and OH LIF signal as a function of the flame distance from the 12 flame along its normal divided by the laminar flame thickness, n/δ_L . Near the flame front 13 contour at $n/\delta_L=0$, θ is approximately zero, indicating that the temperature gradients are well 14 aligned with the OH LIF gradients. At distances beyond $\delta_L/2$, the assumption starts to break 15 16 down as the angle increases.

17

18 4.4. Thermal dissipation scales

The propagation of reactions in a flame depends on the effective generation and dissipation of turbulent structures throughout the flame [5] [6], allowing the increase in the mean rate of reaction throughout the flame. The distribution and characteristic width of the structures generally follow that of a passive scalar, but are significantly affected by the local temperatures, which increase the diffusivity and viscosity, thus suppressing turbulence, and increasing length scales. This has been shown to be true in diffusion flames [23] [24]; here we demonstrate the similarities and differences for swirling premixed flames. Instantaneous images of the thermal dissipation structures are shown in Fig. 6: for the non-swirling case (left), the structures are associated primarily with the flame, and evolve slowly as the turbulence develops downstream. For the high swirl case, the structures are widely distributed, owing to the higher turbulence and entrainment of outside air. Yet these structures become thicker towards the product region (towards the right of each image).

6 In Figure 7, the dissipation structures are characterized by considering the probability 7 density functions (pdf) of their width, λ_{D} , as a function of the temperature across the flames. 8 The pdfs are conditioned to the temperature of the structure, so that the modes are not 9 representative of the overall image, as the integral of each pdf in Fig. 7 is unity. In general, 10 the structures become systematically thicker towards the high temperature regions, owing to the combined effects of dilatation and increasing viscosity with temperature. Beyond 1400 K, 11 12 detectable structure widths are mostly a result of the noise remaining from the beam steering correction. For the non-swirling flame SwB1, the most probable width of 600 µm appears at 13 14 1000 K and corresponds closely to the unstrained laminar flame thickness of 588 µm. For the 15 high swirl case SwB3, the PDF of layer widths has a peak around 300 µm at 400 K, arising 16 from the mixing of product and fresh reactants via entrainment. Less frequent, thicker flame 17 structures appear as temperature increases, to values approximating the width of the 18 unstrained laminar flame, as in case SwB1. In case SwB3, the width of the PDF distributions increases with temperature, and the overall unconditioned PDF distribution is significantly 19 20 broader than in the non-swirl case.

Turbulent combustion models rely on the relationship between statistical variances of the gradients of the reaction progress variable that represents micromixing and the average reaction rate. DNS studies have been used to scale and adjust models based on such correlations [5] [6] [7] [8]. Previous models for scalar dissipation suggest a linear correlation between the Favre mean scalar dissipation of the reaction progress variable, $\tilde{\chi}_c$,

14

and the variance of the relevant progress variable, $\tilde{c}^{"}$. Specifically, the work by Kolla *et al.* 1 2 [30] and references therein based on the original Bray model [35] suggest a specific 3 correlation for the normalized Favre averaged scalar dissipation of a reaction progress 4 variable to its variance, with a coefficient of order unity in the ideal case of high Da. Using 5 temperature as the progress of reaction, normalized by ΔT , the temperature rise for the 6 adiabatic flame (1622 K for ϕ =0.75), it is possible to reproduce these quantities (Fig. 8) in the form of the normalized Favre averaged scalar dissipation $\hat{\chi}_c = \tilde{\chi}_T \tau_f = \frac{\tau_f}{\Delta T \bar{\rho}} <$ 7 $\rho \alpha |\nabla T''|^2 >$, where $\tau_f = \frac{\delta_L}{S_L}$ is the laminar flame transit time. The laminar flame transit 8 9 time and the density were estimated from the temperature measurements, but variations in mixture composition were neglected. Values for $\hat{\chi}_c$ are plotted as a function of the Favre 10 averaged normalized variance in temperature as progress of reaction, $\tilde{c''^2} = \tilde{T''^2} / \Delta T^2 =$ 11 $\langle (\rho/\bar{\rho}) (T - \tilde{T})^2 \rangle / \Delta T^2$, and colored by the local mean temperature $\langle T \rangle$. 12

The plots in Fig. 8 for FOV1 and FOV2 of SwB1 show two branches, corresponding to 13 14 the higher and lower temperature regions of the flame, reflecting the temperature dependence 15 of the thermal diffusivity. Further away from the base, additional turbulence is generated by 16 shear at the edges, the slope becomes lower, and the two branches merge. At this limit, the mean scalar dissipation rate becomes highly correlated with the mean variance in a nearly 17 linear relationship, indicating that the variations in molecular diffusivity have less of an 18 influence. The theory and DNS predictions for the relevant constant suggest that the slope of 19 20 the curve should scale as [30]:

$$\hat{\chi}_c = \frac{1}{\beta} \left[\left(2 \frac{K_c^*}{\theta_T} - C_4 (1 + Ka)^{-0.4} \right) \theta_T + C_3 (1 + Ka^{-0.5})^{-1} Da^{-1} \right] \widetilde{c^{"2}}$$

21 where θ_T is the ratio of absolute product to reactant temperatures, $Da = \tau_T / \tau_f$ is the 22 Dahmköhler number and $Ka = \tau_f / \tau_\eta$ the Karlovitz number, τ_T the integral turbulent time

scales, au_{η} the Kolmogorov time scale, and the remaining quantities are constants. The values 1 of the constants proposed by Kolla *et al.* [30] are approximately $\frac{K_c^*}{\theta_T} = 0.82$ to 0.85, $C_4 =$ 2 1.1, $C_3 = 1.1$ and $\beta = 6.7$, and values for the present mixture are: $\theta_T = 1 + \frac{\Delta T}{T_0} = 6.5$. In the 3 limit of Da and zero Ka, the slope indicated by the model should be 0.53 to 0.58. Higher 4 5 values of turbulence would in general decrease Da and increase Ka. The measured slopes for 6 SwB3 are closer to the limit model than those of SwB1, with the closest agreement at 7 location FOV3. The higher turbulence levels in SwB3 and at FOV3 are consistent with the closer match to the theory. On the other hand, for SwB3 there is significant entrainment and 8 9 mixing, so that one would expect a departure between the correlation between variance and dissipation. Further work connecting the present measurements to local turbulent velocity 10 measurements should enlighten the correlation between theory, experiments and correlations 11 12 extracted from DNS calculations.

13

14

15 Conclusions

The present investigation showed how swirl and the ensuing high turbulence and 16 entrainment significantly disrupt the flame thermal zone in a premixed flame, whilst the high 17 18 temperature reaction zone interface, as marked by the OH contour, remains relatively intact. 19 The temperature at which the maximum OH gradient appears remains relatively unchanged, showing the lowest variance across the flame region, and coinciding with an isocontour of 20 about 1450 K. In support of previous assumptions regarding the alignment of OH and 21 temperature contours, the present experiments showed that indeed, the 2D gradients of OH 22 23 and temperature align well, up to a distance of about one half the laminar flame thickness 24 away from the flame front, with significant deviations beyond that region in the case of 25 swirling flames.

Similarly to previous investigations of diffusion flames, characteristic diffusive widths of the observed thermal structures vary from 300 to 600 microns, from the non-reacting to the higher temperature regions, as a consequence of dilatation and increasing viscosity. The most probable structure widths coincide with the laminar flame thickness in the unswirled, whilst a more uniform distribution of widths appears in the latter case, with a peak at around 400 K temperatures, corresponding to mixing of product and fresh reactants.

7 The Favre-averaged 2D scalar dissipation obtained from the temperature gradients 8 correlates well with the measured variance in the high turbulence regions. In the low 9 turbulence region near the base, the value of the scalar dissipation is not monotonic with the 10 variance of the progress variable and the local temperature. Future work should target 11 understanding the details of these correlations based on the local turbulent velocity 12 characteristics.

13

14

15 Acknowledgements

The Leverhulme Trust funded the collaboration through an International Network grant for Stratified Flames. This work at Sandia was supported by the U.S. Department of Energy, Office of Basic Energy Sciences, Division of Chemical Sciences, Geosciences, and Biosciences. Sandia National Laboratories is a multiprogram laboratory operated by Sandia Corporation, a Lockheed Martin Company, for the U.S. Department of Energy under contract DE-AC04-94-AL85000.

References

- [1] J. F. Driscoll, Prog. Energy Combust. Sci. 34 (2008) 91-134.
- [2] K. N. C. Bray, P. A. Libby, and J. B. Moss, Combust. Flame 61 (1985) 87-102.
- [3] I. G. Shepherd, Proc. Combust. Inst. 26 (1996) 373-379.
- [4] Ö. L. Gülder and G. J. Smallwood, Comb. Sci. Tech. 179 (2007) 191-206.
- [5] D. Veynante and L. Vervisch, Prog. Energy Combust. Sci. 28 (2002) 193-266.
- [6] K. Bray, M. Champion, P. A. Libby, and N. Swaminathan, Combust. Flame 158 (2011) 2017-2022.
- [7] Y. Gao, N. Chakraborty, and N. Swaminathan, Comb. Sci. Tech. 186 (2014) 1309-1337.
- [8] Y. Gao, N. Chakraborty, and N. Swaminathan, J. Comb. 280671 (2014) 29.
- [9] Y.-C. Chen and M. S. Mansour, Proc. Combust. Inst. 27 (1998) 811-818.
- [10] F. T. C. Yuen and G. Ö.L. Proc. Combust. Inst. 34 (2013) 1393-1400.
- [11] M. S. Sweeney, S. Hochgreb, M. J. Dunn, and R. S. Barlow, Combust. Flame 159 (2012) 2912-2929.
- [12] Y. C. Chen and R. W. Bilger, Combust. Flame 131 (2002) 400-435.
- [13] A. Buschmann, F. Dinkelacker, T. Schäfer, M. Schäfer, and J. Wolfrum, Proc. Combust. Inst. 26 (1996) 437-445.
- [14] C. Kortschik, T. Plessing, and N. Peters, Combust. Flame 136 (2004) 43-50.
- [15] C. Duwig, B. Li, Z. S. Li, and M. Aldén, Combust. Flame 159 (2012) 306-316.
- [16] A. J. Aspden, M. S. Day, and J. B. Bell, J. Fluid Mech. 680 (2011) 287-320.
- [17] A. Y. Poludnenko and E. S. Oran, Combust. Flame 157 (2010) 995-1011.
- [18] S. A. Filatyev, J. F. Driscoll, C. D. Carter, and J. M. Donbar, Combust. Flame 141 (2005) 1-21.
- [19] F. T. C. Yuen and Ö. L. Gülder, Proc. Combust. Inst. 34 (2013) 1393-1400.
- [20] P. M. Allison, Y. Chen, M. Ihme, and J. F. Driscoll, Proc. Combust. Inst. 35 (2015) 3255-3262.
- [21] B. Zhou, C. Brackmann, Q. Li, Z. Wang, P. Petersson, Z. Li, *et al.*, Combust. Flame 162 (2015) 2937-2953.
- [22] M. J. Dunn, A. R. Masri, R. W. Bilger, and R. S. Barlow, Flow Turbul. Combust. 85 (2010) 621-648.
- [23] S. A. Kaiser and J. H. Frank, Proc. Combust. Inst. 32 (2009) 1639-1646.
- [24] J. H. Frank and S. A. Kaiser, Exp. Fluids 44 (2008) 221-233.

- [25] G. H. Wang, R. S. Barlow, and N. T. Clemens, Proc. Combust. Inst. 31 (2007) 1525-1532.
- [26] G. H. Wang, N. T. Clemens, R. S. Barlow, and P. L. Varghese, Meas. Sci. Technol. 18 (2007) 1287.
- [27] M. S. Sweeney, S. Hochgreb, M. J. Dunn, and R. S. Barlow, Combust. Flame 159 (2012) 2896-2911.
- [28] R. Zhou, S. Balusamy, M. S. Sweeney, R. S. Barlow, and S. Hochgreb, Combust. Flame 160 (2013) 2017-2028.
- [29] N. Swaminathan and K. N. C. Bray, Combust. Flame 143 (2005) 549-565.
- [30] H. Kolla, J. W. Rogerson, N. Chakraborty, and N. Swaminathan, Combust. Sci. Tech. 181 (2009) 518-535.
- [31] S. A. Kaiser and J. H. Frank, Proc. Combust. Inst. 31 (2007) 1515-1523.
- [32] M. Baum, T. J. Poinsot, D. C. Haworth, and N. Darabiha, J. Fluid Mech. 281 (1994) 1-32.
- [33] B. Gardiner, B. Yan, Z. Qin, G. Smith, D. Crosley, M. Golden, et al. GRI 3.0, available at ">http://www.me.berkeley.edu/gri_mech/>.
- [34] L. P. H. de Goey, T. Plessing, R. T. E. Hermanns, and N. Peters, Proc. Combust. Inst. 30 (2005) 859-866.
- [35] K. N. C. Bray, Symp. Int. Combust. 17 (1979) 223-233.

Figure Captions

Figure 1. Left half: schematic indicating FOV locations for distances above the burner surface. Streamlines and absolute velocity for SwB1 (left half) and SwB3 (right half). Rectangles represent the imaging locations [28].

Figure 2. An example of flame normal extracted from single shot profiles of OH-PLIF. (a) Instantaneous image of normalized OH LIF intensity, (b) temperature field (in K), overlaid with the flame front at the maximum gradient location (black line) and corresponding flame normal (white lines).

Figure 3. Single shot images of normalized OH LIF signal (top rows), temperature (middle rows) in K, and temperature fluctuation, T', relative to the ensemble averaged temperature field, in K (bottom row) for no swirl (left) and high swirl (right). Top panel: FOV3, bottom: FOV1.

Figure 4: Mean (blue line) and rms (blue bars) fluctuation profiles of the temperature, for FOV1-3 along the normal coordinate *n*, where zero is the flame front. Black lines denote the unstrained laminar flame values for $\phi = 0.75$.

Figure 5. Scatter plot of normalized angle (in multiples of π) between the normal directions for contours of temperature and OH as a function of the absolute value of the normalized distance from the flame front, coloured by a temperature index defined as $\Omega = (T - T_o)/(T_{f,0} - T_o)$, where $T_{f,0}$ represents the unstrained laminar flame temperature at the location of maximum gradient of OH at equivalence ratio of 0.75. Magenta lines represent the mean and rms values.

Figure 6. Instantaneous temperature fluctuation gradients for SwB1 and SwB3. Bottom to top: FOV1 to 3. The right hand side of the figure is the product side.

Figure 7. Conditioned probability density functions of λ_D widths conditioned on temperature over a 20 K range.

Figure 8. Scatter plots of normalized Favre-averaged scalar dissipation rate, $\tilde{\chi}_c$, and mean Favre variance of progress variable temperature variance, $\tilde{c}^{"2}$, colored by the corresponding mean local temperature. The SDR is normalized by the term (δ_L/S_L) ; where S_L is the laminar flame speed of the methane/air flame $(S_L = 0.214 \text{ m/s})$ and δ_L is the laminar flame thickness $(\delta_L = 0.588 \text{ mm})$ derived from laminar flame calculations at an equivalence ratio of $\phi = 0.75$. The figures quoted on each panel are the slopes of each correlation.

Table Captions

Table 1. Operating conditions. The velocity of the inner channel is $U_i = 8.3$ m/s (Re_i = 5960) and for the outer channel, $U_o = 18.7$ m/s, (Re_i = 11500 based on hydraulic diameter of the outer annulus) with co-flow velocity $U_{co} = 0.4$ m/s. Coordinates of the center of the FOV in radial and axial distances from the centreline at the base of the burner, in mm. SFR: ratio of incoming tangential to total flow rate.

Table 2. Maximum value of the ratio for the total mean velocity fluctuation U' divided by the laminar speed S_L for a given axial location, z. Turbulent velocity measurements acquired with laser Doppler anemometry (LDA) and particle image velocimetry (PIV) by Zhou *et al.* [28].

Scalar dissipation rate and scales in swirling turbulent premixed flames

M. Mustafa Kamal^{a,c*}, Bruno Coriton^b, Ruigang Zhou^a, Jonathan H. Frank^b, Simone Hochgreb^a

^a Department of Engineering, University of Cambridge, CB2 1PZ, Cambridge, UK ^b Combustion Research Facility, Sandia National Laboratories, Livermore, CA 94551, USA ^c Department of Mechanical Engineering, University of Engineering and Technology, Peshawar, Pakistan

Corresponding author:	M. Mustafa Kamal
	Department of Engineering, University of Cambridge
	Cambridge, CB2 1PZ, United Kingdom
	Fax: (+44) (0) 1223 764311
	Email: mustafa.kamal@cantab.net
Colloquium topic: 5.	Turbulent flames

Alternative Colloquium topic: 3. Diagnostics

Paper length (method 1):

Main Text:	word processor count	=3538
Equations:	(0+0) x (7.6 words/line) x (1 columns)	= 0
References:	$(35+2) \times (2.3 \text{ lines/reference}) \times (7.6 \text{ words/line})$	= 623
Tables:	(7+4) x (7.6 words/line) x (1 columns)	= 84

Figures: Word count = (figure height in mm + 10 mm) x (2.2 words/mm) x (#columns) + (#words in caption)

Figure 1:	$(60 \text{ mm}+10) \times (2.2 \text{ words/mm}) \times (1 \text{ column}) +24$	= 178
Figure 2:	$(33 \text{ mm}+10) \times (2.2 \text{ words/mm}) \times (1 \text{ column}) +38$	= 132
Figure 3:	$(139 \text{ mm}+10) \times (2.2 \text{ words/mm}) \times (1 \text{ column}) +41$	= 368
Figure 4:	$(71 \text{ mm}+10) \times (2.2 \text{ words/mm}) \times (1 \text{ column}) +33$	= 211
Figure 5:	$(104 \text{ mm}+10) \times (2.2 \text{ words/mm}) \times (1 \text{ column}) +56$	= 306
Figure 6:	$(79 \text{ mm}+10) \times (2.2 \text{ words/mm}) \times (1 \text{ column}) +14$	= 209

*Corresponding author *Email address:* mustafa.kamal@cantab.net Figure 7: $(104 \text{ mm}+10) \times (2.2 \text{ words/mm}) \times (1 \text{ column}) +10 = 260$

Figure 8: $(115 \text{ mm}+10) \times (2.2 \text{ words/mm}) \times (1 \text{ column}) +57 = 333$

Total figures: 1965

Total = 6242 words

Color reproduction: online only (color figures are to be printed in gray scale)

Scalar dissipation rate and scales in swirling turbulent premixed flames
 M. Mustafa Kamal^{a,c*}, Bruno Coriton^b, Ruigang Zhou^a, Jonathan H. Frank^b, Simone Hochgreb^a
 ^a Department of Engineering, University of Cambridge, CB2 1PZ, Cambridge, UK
 ^b Combustion Research Facility, Sandia National Laboratories, Livermore, CA 94551, USA
 ^c Department of Mechanical Engineering, University of Engineering and Technology, Peshawar, Pakistan

11 Abstract

12 Simultaneous Rayleigh scattering and OH-PLIF imaging measurements of temperature and OH were used to investigate the properties of turbulent premixed flames, including the 13 14 nature of the 2D thermal structures and scalar dissipation rate in the Cambridge/Sandia 15 swirling bluff body stabilized flames, with and without the effect of swirl. Swirl creates enhanced turbulence as well as outer flow entrainment, and disrupts the pre-flame zone 16 significantly, whilst the high temperature reaction zone as marked by OH remains relatively 17 18 intact. In particular, the temperature at the location of maximum OH gradient shows very low 19 variance across the flame region.

20 The 2D image analysis of OH and temperature shows that the corresponding 2D 21 gradients are aligned up to a distance of half the laminar flame thickness away from the flame front, deviating significantly in the case of swirling flames beyond that region. As in previous 22 investigations in diffusion flames, the mean width of the observed thermal structures 23 24 increases from 300 to 600 microns near the flame, with a main mode around the laminar 25 flame thermal width in the unswirled case. The correlation between 2D thermal fluctuation gradients and variance extracted from the images shows a direct proportionality, with a slope 26 27 which agrees well with theory in the region of high turbulence away from the base. At the

*Corresponding author *Email address:* mustafa.kamal@cantab.net

- base of the flame where turbulence is low, the local scalar dissipation becomes a function of
 the local temperature via the thermal diffusivity.
- 3
- 4
- 5 Keywords: Turbulent premixed flame; Scalar dissipation rate; Dissipative structures; Swirl
- 6 burner; 2D Rayleigh scattering

1 1. Introduction

2 The rate of turbulent micromixing between hot products and reactants controls the overall 3 rate of heat release per unit volume in a flame [1] [2]. In the limit of fast reactions at high 4 Damköhler number (Da), the reaction rate becomes proportional to the scalar dissipation rate, 5 and the flame thickness becomes much smaller than the turbulent spatial scales. Under this 6 thin flame regime, the assumption is often made that the reaction region remains intact, while 7 the reacting interface is transported and extended by turbulence; the reaction rate becomes 8 proportional to the rate at which the flame front propagates through the mixture. This is 9 expressed via the flame surface density [1] [3] [4], or via the rate of scalar dissipation, 10 characterized by the rate of micromixing of the relevant scalar fluctuation [5] [6] [7] [8]. The mean Favre-averaged scalar dissipation rate of a progress of reaction c, is denoted as 11 $\tilde{\chi}_c = \overline{\rho D \nabla c'' \nabla c''} / \bar{\rho}$, where ρ and D are the mixture density and scalar diffusivity, and the 12 usual notation is used: bars for average, tilde for density averaged and double primes for 13 14 turbulent fluctuation away from the local Favre mean.

15 Many previous experimental studies have explored the internal structure of premixed 16 turbulent flames, to understand under what conditions the reaction zone structure may be affected by turbulence. A number of studies measured a thickening of the preheating zone 17 18 (also known as thermal or pre-flame zone) due to enhanced transport caused by structures 19 smaller than the preheating zone [9] [10] [11] [12], whereas others [13] [14] suggest a thinning effect. In references [13] [14], simultaneous OH planar laser-induced fluorescence 20 21 (PLIF) and Rayleigh scattering imaging were used to show that for Karlovitz (Ka) numbers 22 up to 20, the reaction zone is undisturbed; subsequent studies showed that much higher 23 values are required to disrupt the flame zone [15].

Direct numerical simulations of high Ka turbulent flames by Aspden *et al.* [16] and Poludnenko and Oran [17] show that although the pre-flame zone is significantly disrupted, the reaction zone remains rather undisturbed, and that the main effect of turbulence is the wrinkling of the reaction zone. A number of experiments have attempted to connect the effects of turbulence intensity and integral length scale to the behaviour of surrogate scalars, showing for example a widening distribution of intermediates such as formaldehyde with increasing turbulence [1] [18] [19] [20] [21] [22]. A full description of the interaction between turbulence and reaction rate remains a key problem in combustion.

7 Previously, Chen and Bilger [12] combined single-plane measurements of OH and two-8 plane measurements of temperature to study the structure of turbulent methane, propane and 9 hydrogen Bunsen flames, for Karlovitz numbers of up to 3 in the hydrocarbon flames and 10 10 in hydrogen flames. These measurements quantified the gradients of temperature, scalar dissipation and a number of statistical properties of these Bunsen flames [12]. Frank and 11 Kaiser used similar techniques with higher resolution [23] [24] for measurements of thermal 12 13 dissipation rate and length scales in diffusion flames. Wang et al. [25] [26] analysed the 14 resolution requirements for separating noise from signal in scalar dissipation measurements.

15 The present measurements are based on the same techniques developed by Frank and 16 Kaiser [23] [24] for measurements of thermal dissipation rate and corresponding length scales in diffusion flames. The present imaging measurements address the scalar structures in the 17 swirling, bluff-body stabilized methane V-flames extensively described by Sweeney et al. 18 19 [11], at Ka numbers up to 7. These complement previous measurements in turbulent 20 premixed and stratified flames by Sweeney et al. [11] [27] [28] using line Raman/Rayleigh/CO-LIF and cross-planar OH-PLIF techniques. The latter provided detailed 21 22 information on local concentrations of major species and temperature, as well as the local temperature gradients at the flame along a line, and corresponding 3D gradients at the flame 23 24 front. However, such line measurements cannot offer insight into the detailed structure of 25 mixing and scalar dissipation rate in the flow.

In the present work, we use high resolution Rayleigh scattering and OH LIF imaging to measure the 2D length scales of the characteristic structures, as well as the 2D thermal dissipation rate, for the same premixed flames at no swirl and high swirl conditions. The analysis also examines the assumption of alignment between the temperature and OH gradient, used in previous papers [11], and the robustness of the relationship between dissipation rate and variance suggested by turbulent combustion models [6] [29] [30].

7

8 2. Experimental details

9 2.1. Cambridge/Sandia stratified swirl burner and operating conditions

10 The geometry of the swirl burner is described in detail in Ref. [28]. Long co-annular tubes 11 ensure that a well-developed turbulent flow is delivered to the flame region. A ceramic 12 central bluff body is used to stabilize the flame with minimal heat loss. Flow through the 13 outer annulus is split between an axial and a swirling flow emerging at the base of the burner, 14 providing a maximum swirl flow ratio (SFR) of 0.33 [28].

Imaging measurements were performed at the three locations indicated by the field of view (FOV) regions in Fig. 1. Each field of view is approximately centered at the local midpoint of the flame brush, with dimensions of $24.5 \times 16.3 \text{ mm}^2$ and centreline coordinates as listed in Table 1. A subset of the previously used operating conditions in Ref. [28] is studied in this paper, focusing on comparisons between non-swirling (SFR=0%) and highly swirling (SFR=33%) flames, with no stratification between the inner and outer annuli, with a premixed equivalence ratio of ϕ =0.75 (Table 2).

22

Case	SFR (%)	S (-)	FOV 1	FOV 2	FOV 3
SwB1	0	0.03	(05, 15)	(08, 30)	(11, 50)
SwB3	33	0.54	(13, 15)	(21, 30)	(27, 50)

Table 1. Operating conditions for the flames considered. The velocity of the inner channel is $U_i = 8.3$ m/s (Re_i = 5960) and for the outer channel, $U_o = 18.7$ m/s, (Re_i = 11500 based on hydraulic diameter of the outer annulus) with co-flow velocity $U_{co} = 0.4$ m/s. Coordinates of the center of the FOV in radial and axial distances from the centreline at the base of the burner, in mm. SFR: ratio of incoming tangential to total flow rate.

6

Flames	$\frac{U'}{S_L}$				
z (mm)	2	10	30	50	
SwB1	11.5	9.7	10.0	9.8	
SwB3	31.8	27.5	17.9	12.9	

8 **Table 2.** Maximum value of the ratio for the total mean velocity fluctuation U' divided by the 9 laminar speed S_L for a given axial location, *z*. Turbulent velocity measurements acquired with laser 10 Doppler anemometry (LDA) and particle image velocimetry (PIV) by Zhou *et al.* [28].

11

7

12 2.2. Optical arrangement

Simultaneous Rayleigh scattering and OH-PLIF imaging measurements were performed
in the Advanced Imaging Laboratory at Sandia National Laboratories. The experimental
arrangement consisted of the high-resolution Rayleigh imaging apparatus described in Ref.
[31], combined with an additional laser/camera system for simultaneous OH-PLIF imaging
[23].

A laser sheet (100 μ m thickness) used for Rayleigh scattering was produced from a frequency-doubled Nd:YAG laser, with an energy of 2.0 J/pulse at 532 nm at a repetition rate of 10 Hz. OH PLIF was excited by the frequency-doubled output of a 10-Hz Nd:YAGpumped dye-laser tuned to 283.01 nm to pump the Q₁(6) transition of the A-X(1,0) band of OH using 1.2 mJ/pulse.

Rayleigh scattering from the probe volume was imaged onto an unintensified interline transfer CCD camera (SensiCam QE, PCO/Cooke). A second interline-transfer camera was

used to image Rayleigh scattering from the air co-flow adjacent to the burner to account for
shot-to-shot variations in the laser profile. The Rayleigh scattering from room temperature air
was used as a reference signal. The background signal was extracted from measurements in
pure air and helium streams which have known Rayleigh scattering cross sections.

5 The expanded laser beams used for Rayleigh scattering and OH-PLIF were overlapped by 6 stacking the beam planes crossing the centreline of the burner along the axial direction. The 7 OH fluorescence emission was imaged onto an intensified CCD camera (Andor DH312T-8 18H-83). The shot-to-shot laser energy fluctuations of $\pm 2\%$ were negligible for the subsection 9 of the dye-laser beam that was used for PLIF imaging. The OH-PLIF images were corrected 10 for variations in the average dye-laser beam profile. The FOV of the Rayleigh camera was a 19.3x14.6 mm² subsection of the 24.5x16.3 mm² region imaged by the OH-PLIF camera. The 11 12 pixel resolution of the Rayleigh scattering measurement was 14 µm/pixel. The resolution of 13 the OH-PLIF camera was approximately 140 µm/pixel and was limited by the resolution of the image intensifier. 14

Both OH PLIF images and Rayleigh images were smoothed using a Gaussian filter, with the latter relying on a variable, temperature-dependent kernel as described in [31] [24]. Additional information regarding the image processing and system setup are detailed in the relevant references. A fixed Rayleigh scattering cross section equal to 1.09 times that of air was used to determine the temperature for all conditions in Table 1. The maximum uncertainty in the temperature measurement resulting from composition variations was estimated as $\pm 3-4\%$.

1 **3. Data analysis**

Figures 2a and 2b show an example of normalized OH LIF signal and the temperature obtained from the Rayleigh scattering signal, respectively. The flame front location is defined here as the location of the maximum gradient of the OH PLIF signal [32], and is indicated by a black line in the figure. For the present comparisons, this definition provides a well defined reference that is expected to be near the location of peak heat release rate [32]. The local flame normal is defined with respect to the flame front contour, and is shown as white dashed lines in the figure.

9 Local ensemble averaged temperatures $\langle T \rangle$ and the corresponding root mean squared 10 temperature fluctuations $\langle T' \rangle$ are obtained from 2000 individual shots for each FOV. A 11 local flame temperature T_f is defined as the instantaneous temperature at the flame front. 12 Deviations of temperature relative to the instantaneous local flame temperature are defined 13 along the normal coordinate *n*, as $T'_f = T - T_f$, with corresponding mean and rms values, 14 $\langle T_f \rangle$ and $\langle T'_f \rangle$, respectively.

The 2D temperature gradients $\nabla T = \frac{dT}{dr}\mathbf{i} + \frac{dT}{dz}\mathbf{k}$ are determined via first order central 15 differencing after filtering. The gradients of the temperature fluctuations are defined as 16 $\nabla T' = \nabla (T - \langle T \rangle)$. In previous line measurements [11], the 3D temperature gradients 17 18 throughout the flame were assumed to be parallel to the flame normal obtained from the cross 19 planar OH PLIF measurements. Here we assess the quality of this assumption in 2D by 20 determining the statistics of the angle θ between the temperature and OH gradients as a function of temperature. Further, the characteristic 2D thermal diffusion width, λ_D , of the 21 22 dissipation layer is obtained from the images. The diffusion width is defined as the full width at 20% of the local maximum temperature gradient, as determined along the direction normal 23 24 to the layer, which provides a more direct measure of the structure length scale than is 25 possible with 1D measurements [24]. The value of the thermal diffusivity, α , is obtained by 1 interpolating a lookup table of calculated values as a function of temperature from premixed 2 unstrained flames at premixed conditions of ϕ =0.75.

3

4 **4. Results and discussion**

5

6 4.1. Single shot measurements

7 Single shot images of OH PLIF signal, temperature and respective fluctuations for both 8 flow conditions at the regions nearest to the base, FOV1 (bottom panel), and furthest away, 9 FOV3 (top panel), are shown in Fig. 3. For the non-swirling case, SwB1, a comparison of the 10 temperature and OH PLIF images shows that the overall topologies of the OH-PLIF images are well aligned with the temperature images, even in the furthest downstream regions where 11 turbulence is more developed. The flame front contour (location of the highest gradient OH 12 13 signal) overlaps almost exactly with an isotherm at approximately 1450 K throughout the 14 flame region, with a thermal thickness that is only slightly larger than the laminar flame 15 thickness of $\delta_L = 588 \,\mu\text{m}$ calculated for $\phi = 0.75$.

16 Contrast this behavior with the swirling case, SwB3 (Fig. 3, right), in which the preheating region is highly disrupted and convoluted, particularly in the region further 17 downstream (FOV3): regions of high temperature appear in the reactant region, which could 18 19 be a result of out-of-plane motion of neighboring regions of the flame, as well as entrainment 20 of the flame structures into the reaction zone. The product temperatures are lower than in SwB1 as a result of the swirl-induced entrainment of co-flow air into the central product zone 21 22 [11] [28]. The OH PLIF signal boundary and the corresponding flame contour is significantly distorted but not dispersed throughout the pre-heating zone. Although the OH radical is not a 23 definitive marker of the flame location under all conditions, the distribution of the OH PLIF 24

1 signal is very different from that of the temperature. For temperatures above 1200 K, there 2 are no clearly detectable thermal structures.

3

The third row in each panel of Fig. 3 shows the instantaneous fluctuation, T', relative to 4 the local mean temperature for the two regions FOV 1 and FOV 3. The highest deviations 5 from the mean temperature straddle the location of the flame, as expected.

6

7 4.2. Flame temperature statistics

8 Figure 4 shows ensemble mean temperatures and rms fluctuations along the coordinate 9 normal to the flame, n, where n=0 is the flame front defined as the location of maximum gradient in the OH LIF signal. The variance is lowest at n=0, increases to a maximum away 10 11 from the flame front, and eventually decreases to zero in the products and reactants. Laminar 12 unstrained premixed flame simulations at $\phi = 0.75$ (based on GRI Mech 3.0 [33] and full 13 transport properties) are also shown. The measured maximum conditional mean temperatures in the present dataset appear to be systematically lower than the calculated adiabatic flame 14 temperature (which agrees well with the line measurements in [11]), by 150 K in the non-15 swirl case. The sources of the discrepancies are unclear, as all calibrations and procedures 16 17 have been checked.

18 The mean product temperature in the swirling case SwB3 is lower than the corresponding 19 non-swirling case SwB1 owing to entrainment. The fluctuation in temperature is significantly 20 increased by the addition of swirl, particularly in the pre-flame region, due to entrainment of 21 air, both around the outer edges of the flame, as well as through the top in the open 22 recirculation zone [11] [28]. The low fluctuation in temperature at the flame front shows that 23 the location of peak OH gradient, and presumably the reaction zone, is tied to a particular 24 temperature, indicating that the flames appear as curved and strained flamelets.

25

1 4.3. Temperature and OH 2D gradient alignment

2 Since temperature and OH are the most easily imaged scalars, these are often used as 3 surrogates for progress of reaction markers [13] [14] [27] [34]. However, it is clear that their 4 behaviour in the present flames can be very different, and that isocontours of temperature do not always align with those of OH LIF signals. In the present study, it is possible to identify, 5 6 in 2D, how well the isoscalars align around the flame. In particular, in the study using line 7 measurements [11], two-plane OH LIF imaging was used to determine the orientation of the 8 3D flame normal for the flame crossing the measurement line. This orientation was then used 9 to correct the temperature gradient along the measurement line, under the assumption that the 10 OH contour is parallel to the temperature contour in the vicinity of the thermal zone. Figure 5 11 shows how well this assumption holds by evaluating the angle between the normal directions for contours of temperature and OH LIF signal as a function of the flame distance from the 12 flame along its normal divided by the laminar flame thickness, n/δ_L . Near the flame front 13 contour at $n/\delta_L=0$, θ is approximately zero, indicating that the temperature gradients are well 14 aligned with the OH LIF gradients. At distances beyond $\delta_L/2$, the assumption starts to break 15 16 down as the angle increases.

17

18 4.4. Thermal dissipation scales

The propagation of reactions in a flame depends on the effective generation and dissipation of turbulent structures throughout the flame [5] [6], allowing the increase in the mean rate of reaction throughout the flame. The distribution and characteristic width of the structures generally follow that of a passive scalar, but are significantly affected by the local temperatures, which increase the diffusivity and viscosity, thus suppressing turbulence, and increasing length scales. This has been shown to be true in diffusion flames [23] [24]; here we demonstrate the similarities and differences for swirling premixed flames. Instantaneous images of the thermal dissipation structures are shown in Fig. 6: for the non-swirling case (left), the structures are associated primarily with the flame, and evolve slowly as the turbulence develops downstream. For the high swirl case, the structures are widely distributed, owing to the higher turbulence and entrainment of outside air. Yet these structures become thicker towards the product region (towards the right of each image).

6 In Figure 7, the dissipation structures are characterized by considering the probability 7 density functions (pdf) of their width, λ_{D} , as a function of the temperature across the flames. 8 The pdfs are conditioned to the temperature of the structure, so that the modes are not 9 representative of the overall image, as the integral of each pdf in Fig. 7 is unity. In general, 10 the structures become systematically thicker towards the high temperature regions, owing to the combined effects of dilatation and increasing viscosity with temperature. Beyond 1400 K, 11 12 detectable structure widths are mostly a result of the noise remaining from the beam steering correction. For the non-swirling flame SwB1, the most probable width of 600 µm appears at 13 14 1000 K and corresponds closely to the unstrained laminar flame thickness of 588 µm. For the 15 high swirl case SwB3, the PDF of layer widths has a peak around 300 µm at 400 K, arising 16 from the mixing of product and fresh reactants via entrainment. Less frequent, thicker flame 17 structures appear as temperature increases, to values approximating the width of the 18 unstrained laminar flame, as in case SwB1. In case SwB3, the width of the PDF distributions increases with temperature, and the overall unconditioned PDF distribution is significantly 19 20 broader than in the non-swirl case.

Turbulent combustion models rely on the relationship between statistical variances of the gradients of the reaction progress variable that represents micromixing and the average reaction rate. DNS studies have been used to scale and adjust models based on such correlations [5] [6] [7] [8]. Previous models for scalar dissipation suggest a linear correlation between the Favre mean scalar dissipation of the reaction progress variable, $\tilde{\chi}_c$,

14

and the variance of the relevant progress variable, $\tilde{c}^{"}$. Specifically, the work by Kolla *et al.* 1 2 [30] and references therein based on the original Bray model [35] suggest a specific 3 correlation for the normalized Favre averaged scalar dissipation of a reaction progress 4 variable to its variance, with a coefficient of order unity in the ideal case of high Da. Using 5 temperature as the progress of reaction, normalized by ΔT , the temperature rise for the 6 adiabatic flame (1622 K for ϕ =0.75), it is possible to reproduce these quantities (Fig. 8) in the form of the normalized Favre averaged scalar dissipation $\hat{\chi}_c = \tilde{\chi}_T \tau_f = \frac{\tau_f}{\Delta T \bar{\rho}} <$ 7 $\rho \alpha |\nabla T''|^2 >$, where $\tau_f = \frac{\delta_L}{S_L}$ is the laminar flame transit time. The laminar flame transit 8 9 time and the density were estimated from the temperature measurements, but variations in mixture composition were neglected. Values for $\hat{\chi}_c$ are plotted as a function of the Favre 10 averaged normalized variance in temperature as progress of reaction, $\widetilde{c''^2} = \widetilde{T''^2} / \Delta T^2 =$ 11 $\langle (\rho/\bar{\rho}) (T - \tilde{T})^2 \rangle / \Delta T^2$, and colored by the local mean temperature $\langle T \rangle$. 12

The plots in Fig. 8 for FOV1 and FOV2 of SwB1 show two branches, corresponding to 13 14 the higher and lower temperature regions of the flame, reflecting the temperature dependence 15 of the thermal diffusivity. Further away from the base, additional turbulence is generated by 16 shear at the edges, the slope becomes lower, and the two branches merge. At this limit, the mean scalar dissipation rate becomes highly correlated with the mean variance in a nearly 17 linear relationship, indicating that the variations in molecular diffusivity have less of an 18 influence. The theory and DNS predictions for the relevant constant suggest that the slope of 19 20 the curve should scale as [30]:

$$\hat{\chi}_c = \frac{1}{\beta} \left[\left(2 \; \frac{K_c^*}{\theta_T} - C_4 (1 + Ka)^{-0.4} \right) \theta_T + C_3 (1 + Ka^{-0.5})^{-1} Da^{-1} \right] \widetilde{c''^2}$$

21 where θ_T is the ratio of absolute product to reactant temperatures, $Da = \tau_T / \tau_f$ is the 22 Dahmköhler number and $Ka = \tau_f / \tau_\eta$ the Karlovitz number, τ_T the integral turbulent time

scales, au_{η} the Kolmogorov time scale, and the remaining quantities are constants. The values 1 of the constants proposed by Kolla *et al.* [30] are approximately $\frac{K_c^*}{\theta_T} = 0.82$ to 0.85, $C_4 =$ 2 1.1, $C_3 = 1.1$ and $\beta = 6.7$, and values for the present mixture are: $\theta_T = 1 + \frac{\Delta T}{T_0} = 6.5$. In the 3 limit of Da and zero Ka, the slope indicated by the model should be 0.53 to 0.58. Higher 4 5 values of turbulence would in general decrease Da and increase Ka. The measured slopes for 6 SwB3 are closer to the limit model than those of SwB1, with the closest agreement at 7 location FOV3. The higher turbulence levels in SwB3 and at FOV3 are consistent with the 8 closer match to the theory. On the other hand, for SwB3 there is significant entrainment and 9 mixing, so that one would expect a departure between the correlation between variance and dissipation. Further work connecting the present measurements to local turbulent velocity 10 measurements should enlighten the correlation between theory, experiments and correlations 11 12 extracted from DNS calculations.

13

14

15 Conclusions

The present investigation showed how swirl and the ensuing high turbulence and 16 entrainment significantly disrupt the flame thermal zone in a premixed flame, whilst the high 17 18 temperature reaction zone interface, as marked by the OH contour, remains relatively intact. 19 The temperature at which the maximum OH gradient appears remains relatively unchanged, 20 showing the lowest variance across the flame region, and coinciding with an isocontour of about 1450 K. In support of previous assumptions regarding the alignment of OH and 21 22 temperature contours, the present experiments showed that indeed, the 2D gradients of OH 23 and temperature align well, up to a distance of about one half the laminar flame thickness 24 away from the flame front, with significant deviations beyond that region in the case of 25 swirling flames.

Similarly to previous investigations of diffusion flames, characteristic diffusive widths of the observed thermal structures vary from 300 to 600 microns, from the non-reacting to the higher temperature regions, as a consequence of dilatation and increasing viscosity. The most probable structure widths coincide with the laminar flame thickness in the unswirled, whilst a more uniform distribution of widths appears in the latter case, with a peak at around 400 K temperatures, corresponding to mixing of product and fresh reactants.

7 The Favre-averaged 2D scalar dissipation obtained from the temperature gradients 8 correlates well with the measured variance in the high turbulence regions. In the low 9 turbulence region near the base, the value of the scalar dissipation is not monotonic with the 10 variance of the progress variable and the local temperature. Future work should target 11 understanding the details of these correlations based on the local turbulent velocity 12 characteristics.

13

14

15 Acknowledgements

The Leverhulme Trust funded the collaboration through an International Network grant for Stratified Flames. This work at Sandia was supported by the U.S. Department of Energy, Office of Basic Energy Sciences, Division of Chemical Sciences, Geosciences, and Biosciences. Sandia National Laboratories is a multiprogram laboratory operated by Sandia Corporation, a Lockheed Martin Company, for the U.S. Department of Energy under contract DE-AC04-94-AL85000.

References

- [1] J. F. Driscoll, Prog. Energy Combust. Sci. 34 (2008) 91-134.
- [2] K. N. C. Bray, P. A. Libby, and J. B. Moss, Combust. Flame 61 (1985) 87-102.
- [3] I. G. Shepherd, Proc. Combust. Inst. 26 (1996) 373-379.
- [4] Ö. L. Gülder and G. J. Smallwood, Comb. Sci. Tech. 179 (2007) 191-206.
- [5] D. Veynante and L. Vervisch, Prog. Energy Combust. Sci. 28 (2002) 193-266.
- [6] K. Bray, M. Champion, P. A. Libby, and N. Swaminathan, Combust. Flame 158 (2011) 2017-2022.
- [7] Y. Gao, N. Chakraborty, and N. Swaminathan, Comb. Sci. Tech. 186 (2014) 1309-1337.
- [8] Y. Gao, N. Chakraborty, and N. Swaminathan, J. Comb. 280671 (2014) 29.
- [9] Y.-C. Chen and M. S. Mansour, Proc. Combust. Inst. 27 (1998) 811-818.
- [10] F. T. C. Yuen and G. Ö.L. Proc. Combust. Inst. 34 (2013) 1393-1400.
- [11] M. S. Sweeney, S. Hochgreb, M. J. Dunn, and R. S. Barlow, Combust. Flame 159 (2012) 2912-2929.
- [12] Y. C. Chen and R. W. Bilger, Combust. Flame 131 (2002) 400-435.
- [13] A. Buschmann, F. Dinkelacker, T. Schäfer, M. Schäfer, and J. Wolfrum, Proc. Combust. Inst. 26 (1996) 437-445.
- [14] C. Kortschik, T. Plessing, and N. Peters, Combust. Flame 136 (2004) 43-50.
- [15] C. Duwig, B. Li, Z. S. Li, and M. Aldén, Combust. Flame 159 (2012) 306-316.
- [16] A. J. Aspden, M. S. Day, and J. B. Bell, J. Fluid Mech. 680 (2011) 287-320.
- [17] A. Y. Poludnenko and E. S. Oran, Combust. Flame 157 (2010) 995-1011.
- [18] S. A. Filatyev, J. F. Driscoll, C. D. Carter, and J. M. Donbar, Combust. Flame 141 (2005) 1-21.
- [19] F. T. C. Yuen and Ö. L. Gülder, Proc. Combust. Inst. 34 (2013) 1393-1400.
- [20] P. M. Allison, Y. Chen, M. Ihme, and J. F. Driscoll, Proc. Combust. Inst. 35 (2015) 3255-3262.
- [21] B. Zhou, C. Brackmann, Q. Li, Z. Wang, P. Petersson, Z. Li, *et al.*, Combust. Flame 162 (2015) 2937-2953.
- [22] M. J. Dunn, A. R. Masri, R. W. Bilger, and R. S. Barlow, Flow Turbul. Combust. 85 (2010) 621-648.
- [23] S. A. Kaiser and J. H. Frank, Proc. Combust. Inst. 32 (2009) 1639-1646.
- [24] J. H. Frank and S. A. Kaiser, Exp. Fluids 44 (2008) 221-233.

- [25] G. H. Wang, R. S. Barlow, and N. T. Clemens, Proc. Combust. Inst. 31 (2007) 1525-1532.
- [26] G. H. Wang, N. T. Clemens, R. S. Barlow, and P. L. Varghese, Meas. Sci. Technol. 18 (2007) 1287.
- [27] M. S. Sweeney, S. Hochgreb, M. J. Dunn, and R. S. Barlow, Combust. Flame 159 (2012) 2896-2911.
- [28] R. Zhou, S. Balusamy, M. S. Sweeney, R. S. Barlow, and S. Hochgreb, Combust. Flame 160 (2013) 2017-2028.
- [29] N. Swaminathan and K. N. C. Bray, Combust. Flame 143 (2005) 549-565.
- [30] H. Kolla, J. W. Rogerson, N. Chakraborty, and N. Swaminathan, Combust. Sci. Tech. 181 (2009) 518-535.
- [31] S. A. Kaiser and J. H. Frank, Proc. Combust. Inst. 31 (2007) 1515-1523.
- [32] M. Baum, T. J. Poinsot, D. C. Haworth, and N. Darabiha, J. Fluid Mech. 281 (1994) 1-32.
- [33] B. Gardiner, B. Yan, Z. Qin, G. Smith, D. Crosley, M. Golden, et al. GRI 3.0, available at http://www.me.berkeley.edu/gri_mech/>.
- [34] L. P. H. de Goey, T. Plessing, R. T. E. Hermanns, and N. Peters, Proc. Combust. Inst. 30 (2005) 859-866.
- [35] K. N. C. Bray, Symp. Int. Combust. 17 (1979) 223-233.

Figure Captions

Figure 1. Left half: schematic indicating FOV locations for distances above the burner surface. Streamlines and absolute velocity for SwB1 (left half) and SwB3 (right half). Rectangles represent the imaging locations [28].

Figure 2. An example of flame normal extracted from single shot profiles of OH-PLIF. (a) Instantaneous image of normalized OH LIF intensity, (b) temperature field (in K), overlaid with the flame front at the maximum gradient location (black line) and corresponding flame normal (white lines).

Figure 3. Single shot images of normalized OH LIF signal (top rows), temperature (middle rows) in K, and temperature fluctuation, T', relative to the ensemble averaged temperature field, in K (bottom row) for no swirl (left) and high swirl (right). Top panel: FOV3, bottom: FOV1.

Figure 4: Mean (blue line) and rms (blue bars) fluctuation profiles of the temperature, for FOV1-3 along the normal coordinate *n*, where zero is the flame front. Black lines denote the unstrained laminar flame values for $\phi = 0.75$.

Figure 5. Scatter plot of normalized angle (in multiples of π) between the normal directions for contours of temperature and OH as a function of the absolute value of the normalized distance from the flame front, coloured by a temperature index defined as $\Omega = (T - T_o)/(T_{f,0} - T_o)$, where $T_{f,0}$ represents the unstrained laminar flame temperature at the location of maximum gradient of OH at equivalence ratio of 0.75. Magenta lines represent the mean and rms values.

Figure 6. Instantaneous temperature fluctuation gradients for SwB1 and SwB3. Bottom to top: FOV1 to 3. The right hand side of the figure is the product side.

Figure 7. Conditioned probability density functions of λ_D widths conditioned on temperature over a 20 K range.

Figure 8. Scatter plots of normalized Favre-averaged scalar dissipation rate, $\tilde{\chi}_c$, and mean Favre variance of progress variable temperature variance, $\tilde{c}^{"2}$, colored by the corresponding mean local temperature. The SDR is normalized by the term (δ_L/S_L) ; where S_L is the laminar flame speed of the methane/air flame $(S_L = 0.214 \text{ m/s})$ and δ_L is the laminar flame thickness $(\delta_L = 0.588 \text{ mm})$ derived from laminar flame calculations at an equivalence ratio of $\phi = 0.75$. The figures quoted on each panel are the slopes of each correlation.

Table Captions

Table 1. Operating conditions. The velocity of the inner channel is $U_i = 8.3$ m/s (Re_i = 5960) and for the outer channel, $U_o = 18.7$ m/s, (Re_i = 11500 based on hydraulic diameter of the outer annulus) with co-flow velocity $U_{co} = 0.4$ m/s. Coordinates of the center of the FOV in radial and axial distances from the centreline at the base of the burner, in mm. SFR: ratio of incoming tangential to total flow rate.

Table 2. Maximum value of the ratio for the total mean velocity fluctuation U' divided by the laminar speed S_L for a given axial location, z. Turbulent velocity measurements acquired with laser Doppler anemometry (LDA) and particle image velocimetry (PIV) by Zhou *et al.* [28].

Case	SFR (%)	S (-)	FOV 1	FOV 2	FOV 3
SwB1	0	0.03	(05, 15)	(08, 30)	(11, 50)
SwB3	33	0.54	(13, 15)	(21, 30)	(27, 50)

T	a	b	le

Flames	$\frac{U'}{S_L}$				
z (mm)	2	10	30	50	
SwB1	11.5	9.7	10.0	9.8	
SwB3	31.8	27.5	17.9	12.9	

*Figure Click here to download high resolution image





*Figure Click here to download high resolution image









*Figure Click here to download high resolution image



*Figure Click here to download high resolution image

