

# REDUCING EMBODIED CARBON IN THE BUILT ENVIRONMENT: A RESEARCH AGENDA

Francesco Pomponi<sup>1</sup> and Alice Moncaster<sup>1</sup>

<sup>1</sup> Centre for Sustainable Development, Department of Engineering, University of Cambridge, Trumpington Street, CB2 1PZ, United Kingdom

**Keywords:** embodied carbon mitigation, embodied carbon reduction, whole life carbon, low carbon built environment.

## ABSTRACT

*In spite of significant global efforts, the International Energy Agency suggests that buildings-related emissions are on track to double by 2050. Whilst operational energy efficiency continues to receive significant attention by researchers, a less well-researched area is the assessment of embodied carbon in the built environment in order to understand where the greatest opportunities for its mitigation and reduction lie. This paper reports on available mitigation strategies to tackle embodied carbon identified through a systematic review of the available academic evidence. It also investigates the scope and scale of current academic investigations to highlight where significant gaps are for impactful further research on the topic. In total, 17 mitigation strategies have been identified from within the existing literature which have been discussed individually. Results reveal that a one-size-fits-all approach is unlikely to yield beneficial results and future research should be diverse in breadth and scope, locally accurate, and significantly interdisciplinary.*

## INTRODUCTION AND THEORETICAL BACKGROUND

The built environment puts incredible pressure on the natural environment. In the European Union, it accounts for 50% of all extracted materials, 42% of the final energy consumption, 35% of greenhouse gases (GHGs) emissions (EC, 2011) and 32% of waste flows (EEA, 2012), and global figures are not much different (Khasreen et al., 2009). Considerable effort across policy, academia and industry has therefore gone into improving the energy efficiency of buildings. However, until recently political effort has focused almost entirely on the operational stage (occupancy phase) of buildings, with one example being the European Union final deadline for nearly Zero Energy Buildings (nZEB) from 2020 (EU, 2010). The reason given for this focus is that operational energy (and carbon) accounts for the greatest share of life cycle energy (and carbon) of a building.

In spite of these efforts CO<sub>2</sub> emissions are continuing to rise, with the International Energy Agency (IEA) suggesting that emissions are on track to double by 2050 (IEA, 2014). Part of the reason appears to be that the higher energy efficiency leads to rebound effects from increased energy demand, due to, for instance, “more heated space, higher temperatures, and for longer periods” (Rovers, 2014). However a less well-researched reason may be due to the unnecessary dichotomy between operational and embodied impacts, which has the unintended consequences both of ignoring the effects of increased construction and in some cases of shifting the environmental burdens from one life cycle stage (occupancy) to the others (Pomponi et al., 2016a). There is now robust evidence that the embodied impacts of buildings are a significant contributor to global emissions, and that as a percentage of whole life impacts of buildings they can account for more than 50% (Crawford, 2011), with 70% calculated for some cases in the UK (Ibn-Mohammed et al., 2013).

Out of several potential measures, ‘embodied carbon equivalent’ (CO<sub>2e</sub><sup>1</sup>) is useful for several relevant reasons:

- It measures and indicates the contribution of buildings and their products to global warming and climate change, which is increasingly critical (Moncaster, 2015, IPCC, 2014);
- Through considering the carbon intensity of the energy carrier it is more comprehensive than embodied energy (Pomponi et al., 2015);
- While it may not accurately represent all additional ecological and environmental impacts (Pomponi et al., 2016a, Asdrubali et al., 2015a, [Turconi et al., 2013](#)), it correlates well with several impact categories of more comprehensive impact assessment methods (e.g. ReCiPe) (Heinonen et al., 2016), thus acting as a useful indicator also for impacts other than climate change.

The substantial growth of related literature from outside academia (ASPB, 2014, RICS, 2012, UKGBC, 2015, IEA, 2016, ICE, 2015, BRE, 2015), which addresses the themes of EC reduction and mitigation, also confirms the importance of embodied carbon.

In spite of this growing interest and understanding of the issue, the body of academic knowledge on strategies to tackle embodied carbon has not previously been investigated systematically. This paper reports on previous research by the authors (Pomponi and Moncaster, 2016) and presents seventeen

---

<sup>1</sup> Carbon dioxide equivalent emissions, measuring unit of the Global Warming Indicator (GWI)

mitigation strategies that have been identified to address embodied carbon reduction in the built environment.

The following section introduces the method whereas section three discusses each of the mitigation strategies identified and includes the meta-analysis of all collected data to identify existing trends and issues. The fourth section concludes the paper.

## **METHODOLOGY AND METHODS**

The choice of a systematic approach to review the existing literature is done to ensure thoroughness, rigour and objectivity. This approach is widely used in other disciplines ([Tranfield et al., 2003](#), [Delbufalo, 2012](#)) but also in built environment research ([Pomponi et al., 2016b](#)). A further technique often combined with this process is the meta-analysis of data to quantitatively integrate research findings across a wide number of studies ([Delbufalo, 2012](#)) in order to reveal and map significant trends ([Pomponi et al., 2016b](#)) through the harmonised use of reviewed data ([Asdrubali et al., 2015a](#), [Pomponi et al., 2016b](#)). Ultimately, the purpose of a systematic literature review and meta-analysis is to make sense of key elements within a large collection of sometimes-contradictory studies to facilitate decision-making and action with an aim to inform both policymaking and practice ([Tranfield et al., 2003](#)).

In this paper the following strings<sup>2</sup> and combinations thereof have been searched across main literature database<sup>3</sup>:

- Embodied carbon mitigation (+strategy)
- Embodied carbon reduction (+strategy)
- Embodied carbon management (+strategy)
- Embodied carbon building(s)
- Life cycle assessment building(s)
- LCA building(s)
- Life cycle carbon building(s)

Due to the rapidly developing field, search results were temporally limited to 10 years and given existing disputes over reliability, data quality, and system boundaries within LCA, results were also limited to peer-reviewed journal articles. In total, after removing duplicates, 876 manuscripts matched the initial search criteria but only 102 were eventually relevant to this research. Due to the page limit for this paper it was not possible to report all details of the studies reviewed but the interested reader could refer to the full article of the extensive research for more information ([Pomponi and Moncaster, 2016](#)).

## **EMBODIED CARBON MITIGATION STRATEGIES**

Seventeen mitigation strategies (MSs) were identified in the reviewed literature, which are presented and discussed in turn.

---

<sup>2</sup> The search was limited to Title, Abstract, and Keywords of manuscripts to avoid completely unrelated results.

<sup>3</sup> Web of Knowledge, Web of Science, Science Direct and Google Scholar.

## **MS1: Use of materials with lower embodied energy and carbon**

The use of alternative materials with low EE and EC to mitigate the contribution of the built environment to climate change was a particularly common solution (e.g. Yu et al., 2011, Ng et al., 2012). In many studies, this approach involves the use of natural materials (e.g. timber, bamboo, hemp-lime composites). For instance, Reddy (2009) investigated the use of stabilised mud blocks (SMB) as a substitute for load bearing brickwork and found nearly a 50% reduction in embodied costs. With a focus on using alternative building materials over more traditional ones for a 28-storey residential building in Hong Kong, Cui et al. (2011) quantified the related embodied carbon savings, obtaining a 34.8% reduction. Switching from material level to a full house project, Salazar and Meil (2009) assessed the GHG impacts of what they call a 'wood-intensive' house in comparison to a typical one with brick cladding in Canada and found extremely significant differences between the two: 20 tCO<sub>2e</sub> for the former vs. 72 tCO<sub>2e</sub> of the latter. The enormous potential of a broader adoption of wood as a construction material seems confirmed by Upton et al. (2008) who, in a US residential-sector-wide study, indicated savings of 9.6 MtCO<sub>2e</sub>/annum by using wood as an alternative to concrete- and steel-based building systems under the assumption of 1.5 million single-family new houses built each year. Vukotic et al. (2010) also found a timber structure school building to have lower impacts than the steel frame alternative, but recommend that "rather than encouraging debate about which material is 'better' than any other", the best use is made of chosen materials in any particular situation (Vukotic et al., 2010). It is worth noting that in some comparative studies, the use of materials with lower EE/EC may also involve commonly-used materials, such as in the work of You et al. (2011) who found a 4.2% CO<sub>2</sub> reduction in preferring steel-concrete structures over masonry-concrete structures; an aspect which leads to the importance of design discussed in the next sub-section.

## **MS2: Better design**

Good design practice and appropriate choices at the design stage, as well as techniques such as design for deconstruction, were identified as crucial strategies for EC reduction and mitigation. Acquaye and Duffy (2010) conducted an input-output analysis of the Irish construction sector; they suggest that their results showed that better design could have reduced indirect emissions by 20% and direct emissions by 1.6% totalling 3.43 MtCO<sub>2e</sub>. In examining refurbishment of high-rise concrete buildings in Hong Kong, Chau et al. (2012) also found a determinant role of design. They argued that "the most effective option is to maintain 15-30% of the existing structural and non-structural building elements as it can reduce the CO<sub>2</sub> footprint by 17.3%". This view is echoed and supported by Cuéllar-Franca and Azapagic (2012) who reflect on the longevity of decisions taken at the design stage and call for a sustainable home design which considers the impact that design choices exert over the building's life cycle. The centrality of design is also emphasised by Häkkinen et al. (2015) who recommend a gradual and systematic procession through all different phases and stages of design to accurately assess GHG emissions and achieve low-carbon buildings.

## **MS3: Reduction, re-use and recovery of EE/EC intensive construction materials**

Basbagill et al. (2013) investigated in detail the application of LCA to help designers understand and reduce the environmental impacts of building materials and components. They found that by optimising key parameters (e.g. thickness of piles and footings, and of external and internal walls) "anywhere from 63% to 75% reduction in the building's maximum total embodied impact is possible"

(Basbagill et al., 2013). Garcia-Segura et al. (2014) assessed the reduction of GHG emissions due to a reduced use of Portland cement and its substitution with blended cement, which has a higher content of fly ash (FA) and blast furnace slag (BFS). Such an approach promises to lead to 7% - 20% fewer emissions (Garcia-Segura et al., 2014). Similar environmental benefits following a reduction in use of cement are echoed by Atmaca and Atmaca (2015) and Miller and Doh (2015). Moynihan and Allwood (2014) investigated the utilisation of structural steel in buildings and concluded that by designing to minimise the material used rather than the cost, the use of steel in building and the associated embodied impacts could be dramatically reduced.

#### **MS4: Tools, methods, and methodologies**

Despite the populated panorama of existing tools, assessment methods and methodology, it still seems this is seen as a key area to bring about embodied carbon reduction with the parallel aim of building a better and stronger EC culture amongst the built environment stakeholders. This may take the form of coupling EC assessment with building information modelling (BIM) (Ariyaratne and Moncaster, 2014) or combining BIM with dynamic energy simulation tools (Peng, 2016). In some other cases, new methodologies aim at refining existing ones by, for example, coupling a life cycle carbon assessment with an analysis of the value created by the specific activity/product under investigation (Li et al., 2013).

#### **MS5: Policy and regulations (Governments)**

Perhaps unsurprisingly, the implementation and/or revision of policy and regulations by Governments also emerged as a commonly cited strategy for EC reduction (e.g. Dakwale et al., 2011, Blengini and Di Carlo, 2010, Giesekam et al., 2014). In some studies (Giesekam et al., 2014) this strategy is mainly intended as a means to support other mitigation strategies, like a wider use of low EE/EC materials, whereas in others policy has a broader reach. For instance, Dhakal (2010) reports on Chinese and Japanese contexts where a 50% CO<sub>2</sub> reduction could be achieved through the impact of policies on design and construction practices.

#### **MS6: Refurbishment of existing buildings**

A few scholars believe the greatest opportunity for EC mitigation lies with the upkeep of existing buildings. This appears to be especially true in developed countries where the existing building stock forms the vast majority of the built environment. Gaspar and Santos (2015) assessed the potential saving for a detached house in Portugal built in the late 1960s, concluding that refurbishment would be 22% more efficient than demolition and rebuild. A strong case for refurbishments can be also found in the work of Power, who demonstrated that the case for large scale demolitions “is greatly weakened” when considering EC as well as operational figures, for the EC of an average refurbishment project to bring an existing house up to modern standards is around one third of that of a new house (Power, 2008, Power, 2010).

#### **MS7: Decarbonisation of energy supply/grid**

Just as the idea of decarbonising the energy supply is seen as one pathway to operational-carbon-free buildings (Rovers, 2014), some scholars point out that there is the same opportunity for embodied costs (Chang et al., 2011, Heinonen et al., 2011, Jiang and Tovey, 2009). For instance, in

the study from Heinonen et al. (2011) a specific 'greener' energy mix would cut 6% off the total emissions figure.

#### **MS8: Inclusion of waste, by-product, and used materials into building materials**

A further beneficial effect may be brought about by the inclusion of waste and by-products into building materials (e.g. Lee et al., 2011, [Napolano et al., 2015](#)), in light of cradle-to-cradle design and circular economy approaches which have recently received increased attention as a valid and viable alternative to the traditional linear make-use-dispose paradigm. Intini and Kuehtz (2011) investigated the use of recycled plastic bottles to manufacture thermal insulation in Italy and concluded that recycled polyethylene terephthalate (PET) can reduce environmental impact as much as 46% with respect to GWP. Some researchers also highlight the importance of considering the necessary supply chain to realise this (Densley Tingley and Davison, 2011).

#### **MS9: Increased use of local materials**

Several studies reported the EC reduction due to an increased use of local materials which would reduce transportation impacts (e.g. Asdrubali et al., 2015b, Chou and Yeh, 2015, Gustavsson et al., 2010). In a detailed assessment of stone production carried out in accordance to PAS 2050 guidelines, Crishna et al. (2011) argued that depending on the stone type and the country of origin, the use of UK-based stones can save between 2% - 84% of the EC of stones sourced from abroad. It is also worth considering that such strategy would benefit local or national economies as well as the environment.

#### **MS10: Policy and regulations (Construction sector)**

For some scholars, the strength of policies and regulations lies not (or at least not only) with governments but with bodies and stakeholders within the construction sectors (e.g. Acquaye and Duffy, 2010, Alshamrani et al., 2014). For instance, Alshamrani et al. (2014) developed an integrated LCA – LEED model for sustainability assessment and believe there would be positive consequences if it were voluntarily adopted and used in the construction sector.

#### **MS11: Social 'component' - change driven by strong demand from all BE stakeholders**

This cluster groups 'social' elements for a built environment with lower EC, such as an aesthetic demand for "buildings [with] sustainable credentials" ([Monahan and Powell, 2011](#)), or solutions related to people's skills such as the contractors' ability to plan resources, their management skills and construction performance mentioned by Sandanayake et al. (2016). Also, social or cultural aspects have been identified as barriers to EC reduction, such as the inertia of builders towards environmentally conscious regulations in China reported by Li and Colombier (2009).

#### **MS12: More efficient construction processes/techniques**

In some studies, a gain in efficiency in the construction sector is seen as an important opportunity for EC reduction (e.g. Sandanayake et al., 2016, Roberts, 2008, [Monahan and Powell, 2011](#)). This is often intended as a more efficient manufacture of building materials, the use of innovative and less wasteful processes during the construction stage, or a combination of the two. This strategy also includes the reduction of delays, the impact of site conditions, and the use of more energy efficient machinery.

### **MS13: Carbon mitigation offsets, emissions trading, and carbon tax**

Some scholars see the solution to the EC problem in carbon mitigation and trading, and in fewer cases carbon taxing. For instance, Dalene (2012) reports on a case study of a residential building where all “GHG emissions were offset by carbon mitigation programs and certified carbon offsets were purchased” to achieve carbon neutral status. At a broader scale, Kennedy and Sgouridis (2011) developed a carbon accounting framework for cities to categorise and determine urban emissions strategies.

### **MS14: Carbon sequestration**

The carbon sequestration approach found in few studies (e.g. Dhakal, 2010, Gustavsson et al., 2006) is to some extent linked to the previous strategy but it deserves a separate category due to different underlying principles: while carbon offsets and emissions trading offer a policy solution to EC reduction, carbon sequestration looks at the technological side of the issue exploring new materials or innovative uses of existing ones to capture and store carbon. For instance, [Sodagar et al. \(2011\)](#) studied the use of biotic materials in a social housing project in the UK and concluded that the carbon lock-up potential could reduce carbon emissions by 61% over the 60-year lifespan of the houses.

### **MS15: Extending the building's life**

Intuitively, extending a building's life span would delay and therefore reduce the EC associated with deconstruction and demolition, waste processing and rebuild. However, this strategy is only considered by a handful of studies in the existing literature (e.g. [Densley Tingley and Davison, 2011](#), [Toller et al., 2011](#), [Yung and Chan, 2012](#)). In some of the studies, this strategy does not simply consider aiming for a longer service life of the building but is also about designing the building with the necessary flexibility to be durable and adaptable.

### **MS16: Increased use of prefabricated elements/off-site manufacturing**

This category is somewhat linked to more efficient construction processes but due to a clear stream within the existing literature oriented towards off-site manufacturing and prefabrication it was coded separately. In some studies, the emission savings of this strategy alone have been quantified. For instance Mao et al. (2013) found that semi-prefabrication would emit 3.2% less than conventional construction. Off-site manufacturing has been also investigated in combination with other strategies (e.g. the use of low embodied carbon materials) such as in the case of Monahan and Powell (2011).

### **MS17: Demolition and rebuild**

In a very few cases, such as Dubois and Allacker (2015), it has been suggested that a truly significant carbon reduction in the built environment would only be achievable through wide campaigns of demolition and reconstruction with the belief that embodied costs of such activities are negligible compared to the benefits of new build. In another study (Boardman, 2007), a demolition level higher than current practice is considered a “sensible compromise” to tackle climate change.



Table 1 shows the meta-analysis done on the correlation across all mitigation strategies (blue = higher correlation / red = lower correlation).

As evident in Table 1 some MSs are more strongly correlated with others. It is important to clarify that low or null correlation does not necessarily mean that there is not a synergy to exploit between a specific pair of MSs but might as well mean that the potential has not yet been investigated. As such, those specific pairs of MSs are interesting avenues for further collaborative and interdisciplinary research.

*Table 1 - Meta Analysis of Correlation Across All Mitigation Strategies*

MS	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17
1	100%	47%	43%	27%	20%	14%	20%	18%	18%	10%	12%	8%	4%	10%	10%	6%	0%
2		100%	48%	38%	27%	23%	21%	21%	8%	21%	13%	8%	13%	8%	10%	2%	2%
3			100%	29%	10%	24%	10%	24%	14%	2%	5%	5%	5%	10%	12%	5%	0%
4				100%	30%	9%	12%	12%	6%	24%	18%	0%	9%	6%	6%	0%	0%
5					100%	25%	25%	8%	4%	29%	33%	8%	21%	8%	8%	0%	8%
6						100%	16%	11%	16%	5%	16%	5%	5%	11%	5%	5%	0%
7							100%	13%	19%	6%	19%	6%	6%	13%	6%	6%	0%
8								100%	20%	7%	20%	7%	7%	13%	7%	7%	0%
9									100%	8%	23%	8%	8%	15%	8%	8%	0%
10										100%	25%	8%	8%	17%	8%	8%	0%
11											100%	8%	8%	17%	8%	8%	0%
12												100%	11%	22%	11%	11%	0%
13													100%	22%	11%	11%	0%
14														100%	13%	13%	0%
15															100%	14%	0%
16																100%	0%
17																	100%

## CONCLUSIONS

This paper has reported on part of the outcomes of a substantial systematic review of academic knowledge on the topics of life cycle assessment of buildings and embodied carbon reduction in the built environment. We have chosen to develop the paper around the mitigation strategies identified in the existing literature as these might as well form very important directions for future research in the field. The seventeen mitigation strategies span across several disciplines and surely involve a plurality of stakeholders. As a consequence, the problem of EC does require a pluralistic solution because no single mitigation strategy is seen to be effective in EC reduction; this aspect should hopefully foster collaborative and interdisciplinary research even more in the future.

The analysis has also shown the interconnectedness of the role of the designer with those of the researchers, the materials manufacturers and the policy makers. For instance, the development and use of materials with low EC is intertwined with a better design which in turn is seen as the key element to also reduce, re-use and recover EC-intensive construction materials, such as steel and concrete. New tools, methods and methodologies are also needed to facilitate the transition to a low-carbon built environment, as are policies at both government and construction sector levels. These however require support from the society at large (social 'component') if a substantial change



is to be achieved. In developed countries, the upkeep of the existing building stock also stood out as a crucial element. In most cases, this was simply seen as the need to refurbish existing buildings although there are growing signs of more specific research activities in extending the building's life during a refurbishment project in a design-for-longevity aim.

## REFERENCES

- ACQUAYE, A. A. & DUFFY, A. P. 2010. Input–output analysis of Irish construction sector greenhouse gas emissions. *Building and Environment*, 45, 784-791.
- ALSHAMRANI, O. S., GALAL, K. & ALKASS, S. 2014. Integrated LCA–LEED sustainability assessment model for structure and envelope systems of school buildings. *Building and Environment*, 80, 61-70.
- ARIYARATNE, C. I. & MONCASTER, A. M. 2014. Stand-alone calculation tools are not the answer to embodied carbon assessment. *Energy Procedia*, 62, 150-159.
- ASDRUBALI, F., BALDINELLI, G., D’ALESSANDRO, F. & SCRULLA, F. 2015a. Life cycle assessment of electricity production from renewable energies: Review and results harmonization. *Renewable and Sustainable Energy Reviews*, 42, 1113-1122.
- ASDRUBALI, F., D’ALESSANDRO, F. & SCHIAVONI, S. 2015b. A review of unconventional sustainable building insulation materials. *Sustainable Materials and Technologies*, 4, 1-17.
- ASPB 2014. Embodied Carbon Industry Task Force Recommendations - Proposals for Standardised Measurement Method and Recommendations for Zero Carbon Building Regulations and Allowable Solutions.  
[http://www.asbp.org.uk/uploads/documents/resources/Embodied%20Carbon%20Industry%20Task%20Force%20Proposals June%202014 Final%5B1%5D.pdf](http://www.asbp.org.uk/uploads/documents/resources/Embodied%20Carbon%20Industry%20Task%20Force%20Proposals%20June%202014%20Final%5B1%5D.pdf): The Alliance for Sustainable Building Products.
- ATMACA, A. & ATMACA, N. 2015. Life cycle energy (LCEA) and carbon dioxide emissions (LCCO2A) assessment of two residential buildings in Gaziantep, Turkey. *Energy and Buildings*, 102, 417-431.
- BASBAGILL, J., FLAGER, F., LEPECH, M. & FISCHER, M. 2013. Application of life-cycle assessment to early stage building design for reduced embodied environmental impacts. *Building and Environment*, 60, 81-92.
- BLENGINI, G. A. & DI CARLO, T. 2010. Energy-saving policies and low-energy residential buildings: an LCA case study to support decision makers in Piedmont (Italy). *International Journal of Life Cycle Assessment*, 15, 652-665.
- BOARDMAN, B. 2007. Examining the carbon agenda via the 40% House scenario. *Building Research and Information*, 35, 363-378.
- BRE 2015. The Green Guide Explained. BRE Centre for Sustainable Products.  
[http://www.bre.co.uk/filelibrary/greenguide/PDF/The-Green-Guide-Explained March2015.pdf](http://www.bre.co.uk/filelibrary/greenguide/PDF/The-Green-Guide-Explained_March2015.pdf): Building Research Establishment.
- CHANG, Y., RIES, R. J. & WANG, Y. 2011. The quantification of the embodied impacts of construction projects on energy, environment, and society based on I–O LCA. *Energy Policy*, 39, 6321-6330.
- CHAU, C. K., HUI, W. K., NG, W. Y. & POWELL, G. 2012. Assessment of CO2 emissions reduction in high-rise concrete office buildings using different material use options. *Resources Conservation and Recycling*, 61, 22-34.
- CHOU, J.-S. & YEH, K.-C. 2015. Life cycle carbon dioxide emissions simulation and environmental cost analysis for building construction. *Journal of Cleaner Production*, 101, 137-147.
- CRAWFORD, R. H. 2011. *Life Cycle Assessment in the Built Environment*, London, New York, Spon Press.
- CRISHNA, N., BANFILL, P. F. G. & GOODSIR, S. 2011. Embodied energy and CO2 in UK dimension stone. *Resources Conservation and Recycling*, 55, 1265-1273.

- CUÉLLAR-FRANCA, R. M. & AZAPAGIC, A. 2012. Environmental impacts of the UK residential sector: Life cycle assessment of houses. *Building and Environment*, 54, 86-99.
- CUI, H. Z., SHAM, F. C., LO, T. Y. & LUM, H. T. 2011. Appraisal of Alternative Building Materials for Reduction of CO2 Emissions by Case Modeling. *International Journal of Environmental Research*, 5, 93-100.
- DAKWALE, V. A., RALEGAONKAR, R. V. & MANDAVGANE, S. 2011. Improving environmental performance of building through increased energy efficiency: A review. *Sustainable Cities and Society*, 1, 211-218.
- DALENE, F. 2012. Technology and information management for low-carbon building. *Journal of Renewable and Sustainable Energy*, 4.
- DELBUFALO, E. 2012. Outcomes of inter-organizational trust in supply chain relationships: a systematic literature review and a meta-analysis of the empirical evidence. *Supply Chain Management: An International Journal*, 17, 377-402.
- DENSLEY TINGLEY, D. & DAVISON, B. 2011. Design for deconstruction and material reuse. *Proceedings of the Institution of Civil Engineers-Energy*, 164, 195-204.
- DHAKAL, S. 2010. GHG emissions from urbanization and opportunities for urban carbon mitigation. *Current Opinion in Environmental Sustainability*, 2, 277-283.
- DUBOIS, M. & ALLACKER, K. 2015. Energy savings from housing: Ineffective renovation subsidies vs efficient demolition and reconstruction incentives. *Energy Policy*, 86, 697-704.
- EC 2011. Roadmap to a Resource Efficient Europe - Communication from the Commission to the European Parliament, the Council, the European Economic and Social Committee and the Committee of the Regions COM(2011) 571 final. European Commission.
- EEA 2012. Material Resources and Waste - 2012 Update. European Environment Agency. Copenhagen, .
- EU 2010. Directive 2010/31/EU of the European Parliament and of the Council of 19 May 2010 on the energy performance of buildings (recast). Official Journal of the European Union.
- GARCIA-SEGURA, T., YEPES, V. & ALCALA, J. 2014. Life cycle greenhouse gas emissions of blended cement concrete including carbonation and durability. *International Journal of Life Cycle Assessment*, 19, 3-12.
- GASPAR, P. L. & SANTOS, A. L. 2015. Embodied energy on refurbishment vs. demolition: A Southern Europe case study. *Energy and Buildings*, 87.
- GIESEKAM, J., BARRETT, J., TAYLOR, P. & OWEN, A. 2014. The greenhouse gas emissions and mitigation options for materials used in UK construction. *Energy and Buildings*, 78, 202-214.
- GUSTAVSSON, L., JOELSSON, A. & SATHRE, R. 2010. Life cycle primary energy use and carbon emission of an eight-storey wood-framed apartment building. *Energy and Buildings*, 42, 230-242.
- GUSTAVSSON, L., PINGOUD, K. & SATHRE, R. 2006. Carbon dioxide balance of wood substitution: comparing concrete-and wood-framed buildings. *Mitigation and adaptation strategies for global change*, 11, 667-691.
- HÄKKINEN, T., KUITTINEN, M., RUUSKA, A. & JUNG, N. 2015. Reducing embodied carbon during the design process of buildings. *Journal of Building Engineering*, 4, 1-13.
- HEINONEN, J., SAYNAJOKI, A. & JUNNILA, S. 2011. A Longitudinal Study on the Carbon Emissions of a New Residential Development. *Sustainability*, 3, 1170-1189.
- HEINONEN, J., SÄYNÄJOKI, A., JUNNONEN, J.-M., PÖYRY, A. & JUNNILA, S. 2016. Pre-use phase LCA of a multi-story residential building: Can greenhouse gas emissions be used as a more general environmental performance indicator? *Building and Environment*, 95, 116-125.

- IBN-MOHAMMED, T., GREENOUGH, R., TAYLOR, S., OZAWA-MEIDA, L. & ACQUAYE, A. 2013. Operational vs. embodied emissions in buildings—A review of current trends. *Energy and Buildings*, 66, 232-245.
- ICE 2015. Energy Briefing Sheet: Embodied Energy and Carbon. <https://www.ice.org.uk/disciplines-and-resources/briefing-sheet/embodied-energy-and-carbon>: Institution of Civil Engineers.
- IEA 2014. Technology Roadmap. Energy efficient building envelopes. Paris, France: International Energy Agency.
- IEA 2016. Annex 57 Evaluation of Embodied Energy & Embodied GHG Emissions for Building Construction - Report of Subtask 4: Recommendations for the reduction of embodied carbon and energy from buildings. International Energy Agency.
- INTINI, F. & KUEHTZ, S. 2011. Recycling in buildings: an LCA case study of a thermal insulation panel made of polyester fiber, recycled from post-consumer PET bottles. *International Journal of Life Cycle Assessment*, 16, 306-315.
- IPCC 2014. *Intergovernmental Panel on Climate Change - Climate Change 2014: Impacts, Adaptation, and Vulnerability*, Cambridge, UK; New York, NY, USA, Cambridge University Press.
- JIANG, P. & TOVEY, N. K. 2009. Opportunities for low carbon sustainability in large commercial buildings in China. *Energy Policy*, 37, 4949-4958.
- KENNEDY, S. & SGOURIDIS, S. 2011. Rigorous classification and carbon accounting principles for low and Zero Carbon Cities. *Energy Policy*, 39, 5259-5268.
- KHASREEN, M., BANFILL, P. F. & MENZIES, G. 2009. Life-Cycle Assessment and the Environmental Impact of Buildings: A Review. *Sustainability*, 1, 674-701.
- LEE, B., TRCKA, M. & HENSEN, J. L. 2011. Embodied energy of building materials and green building rating systems—a case study for industrial halls. *Sustainable Cities and Society*, 1, 67-71.
- LI, D. Z., CHEN, H. X., HUI, E. C. M., ZHANG, J. B. & LI, Q. M. 2013. A methodology for estimating the life-cycle carbon efficiency of a residential building. *Building and Environment*, 59, 448-455.
- LI, J. & COLOMBIER, M. 2009. Managing carbon emissions in China through building energy efficiency. *Journal of Environmental Management*, 90, 2436-2447.
- MAO, C., SHEN, Q., SHEN, L. & TANG, L. 2013. Comparative study of greenhouse gas emissions between off-site prefabrication and conventional construction methods: Two case studies of residential projects. *Energy and Buildings*, 66, 165-176.
- MILLER, D. & DOH, J.-H. 2015. Incorporating sustainable development principles into building design: a review from a structural perspective including case study. *Structural Design of Tall and Special Buildings*, 24, 421-439.
- MONAHAN, J. & POWELL, J. C. 2011. An embodied carbon and energy analysis of modern methods of construction in housing: A case study using a lifecycle assessment framework. *Energy and Buildings*, 43, 179-188.
- MONCASTER, A. 2015. Pathways to Low Carbon Building: Reflection on the Special Issue. *Buildings*, 5, 751.
- MOYNIHAN, M. C. & ALLWOOD, J. M. 2014. Utilization of structural steel in buildings. *Proceedings of the Royal Society a-Mathematical Physical and Engineering Sciences*, 470.
- NAPOLANO, L., MENNA, C., ASPRONE, D., PROTA, A. & MANFREDI, G. 2015. LCA-based study on structural retrofit options for masonry buildings. *International Journal of Life Cycle Assessment*, 20, 23-35.
- NG, S. T., WONG, J. M. W., SKITMORE, S. & VERONIKA, A. 2012. Carbon dioxide reduction in the building life cycle: a critical review. *Proceedings of the Institution of Civil Engineers-Engineering Sustainability*, 165, 281-292.

- PENG, C. 2016. Calculation of a building's life cycle carbon emissions based on Ecotect and building information modeling. *Journal of Cleaner Production*.
- POMPONI, F. & MONCASTER, A. M. 2016. Embodied Carbon Mitigation and Reduction in the Built Environment – What Does the Evidence Say? *Journal of Environmental Management (under review)*.
- POMPONI, F., PIROOZFAR, P. A. E. & FARR, E. R. P. 2016a. An Investigation into GHG and non-GHG Impacts of Double Skin Façades in Office Refurbishments. *Journal of Industrial Ecology*, 20, 234-248.
- POMPONI, F., PIROOZFAR, P. A. E., SOUTHALL, R., ASHTON, P. & FARR, E. R. P. 2015. Life cycle energy and carbon assessment of double skin façades for office refurbishments. *Energy and Buildings*, 109, 143-156.
- POMPONI, F., PIROOZFAR, P. A. E., SOUTHALL, R., ASHTON, P. & FARR, E. R. P. 2016b. Energy performance of Double-Skin Façades in temperate climates: A systematic review and meta-analysis. *Renewable and Sustainable Energy Reviews*, 54, 1525-1536.
- POWER, A. 2008. Does demolition or refurbishment of old and inefficient homes help to increase our environmental, social and economic viability? *Energy Policy*, 36, 4487-4501.
- POWER, A. 2010. Housing and sustainability: demolition or refurbishment? *Proceedings of the ICE-Urban Design and Planning*, 163, 205-216.
- REDDY, B. V. 2009. Sustainable materials for low carbon buildings. *International Journal of Low-Carbon Technologies*, 4, 175-181.
- RICS 2012. Methodology to calculate embodied carbon of materials - RICS information paper. Produced by the Embodied Carbon Working Group of the Royal Institution of Chartered Surveyors. London
- ROBERTS, S. 2008. Effects of climate change on the built environment. *Energy Policy*, 36, 4552-4557.
- ROVERS, R. 2014. Zero-Energy and Beyond: A Paradigm Shift in Assessment. *Buildings*, 5, 1.
- SALAZAR, J. & MEIL, J. 2009. Prospects for carbon-neutral housing: the influence of greater wood use on the carbon footprint of a single-family residence. *Journal of Cleaner Production*, 17, 1563-1571.
- SANDANAYAKE, M., ZHANG, G. & SETUNGE, S. 2016. Environmental emissions at foundation construction stage of buildings – Two case studies. *Building and Environment*, 95, 189-198.
- SODAGAR, B., RAI, D., JONES, B., WIHAN, J. & FIELDSON, R. 2011. The carbon-reduction potential of straw-bale housing. *Building Research and Information*, 39, 51-65.
- TOLLER, S., WADESKOG, A., FINNVEDEN, G., MALMQVIST, T. & CARLSSON, A. 2011. Energy Use and Environmental Impacts of the Swedish Building and Real Estate Management Sector. *Journal of Industrial Ecology*, 15, 394-404.
- TRANFIELD, D. R., DENYER, D. & SMART, P. 2003. Towards a methodology for developing evidence-informed management knowledge by means of systematic review. *British journal of management*, 14, 207-222.
- TURCONI, R., BOLDRIN, A. & ASTRUP, T. 2013. Life cycle assessment (LCA) of electricity generation technologies: Overview, comparability and limitations. *Renewable and Sustainable Energy Reviews*, 28, 555-565.
- UKGBC 2015. Tackling Embodied Carbon in Buildings. Campaign for a Sustainable Built Environment. UK Green Building Council.
- UPTON, B., MINER, R., SPINNEY, M. & HEATH, L. S. 2008. The greenhouse gas and energy impacts of using wood instead of alternatives in residential construction in the United States. *Biomass and Bioenergy*, 32, 1-10.

- VUKOTIC, L., FENNER, R. A. & SYMONS, K. 2010. Assessing embodied energy of building structural elements. *Proceedings of the Institution of Civil Engineers-Engineering Sustainability*, 163, 147-158.
- [YOU, F., HU, D., ZHANG, H., GUO, Z., ZHAO, Y., WANG, B. & YUAN, Y. 2011. Carbon emissions in the life cycle of urban building system in China—A case study of residential buildings. \*Ecological Complexity\*, 8, 201-212.](#)
- YU, D., TAN, H. & RUAN, Y. 2011. A future bamboo-structure residential building prototype in China: Life cycle assessment of energy use and carbon emission. *Energy and Buildings*, 43, 2638-2646.
- [YUNG, E. H. & CHAN, E. H. 2012. Implementation challenges to the adaptive reuse of heritage buildings: Towards the goals of sustainable, low carbon cities. \*Habitat International\*, 36, 352-361.](#)